ISO 307:2007-05 (E)

Plastics - Polyamides - Determination of viscosity number

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Principle 3

5 Reagents and materials 3
5.1 Solvents and reagents 3
5.2 Cleaning liquids 4

6 Apparatus 4

7 Preparation of test samples 5
7.1 General 5
7.2 Samples containing less than 98 % (by mass) polyamide 5

8 Calculation of test portion 6

9 Selection of solvent 6

10 Procedure 7
10.1 Cleaning of the viscometer 7
10.2 Preparation of test solution 7
10.3 Measurement of flow times 9

11 Expression of results 10

12 Repeatability and reproducibility 10

13 Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents 11

14 Test report 11

Annex A (informative) Determination of the concentration of commercial sulfuric acid (95 % to 98 %) and adjustment to 96 % by titration 13

Annex B (informative) Determination of the concentration of sulfuric acid (95 % to 98 %) and adjustment to 96 % by flow time measurement in a small capillary viscometer 16

Annex C (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by titration 18

Annex D (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by density measurement 20

Annex E (informative) Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents 23

Bibliography 33