ISO/TR 10465-3:2007-09 (E)

Underground installation of flexible glass-reinforced pipes based on unsaturated polyester resin (GRP-UP) - Part 3: I nstallation parameters and application limits

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Symbols and abbreviated terms 1

4 Parameters for deflection calculations when using an ATV-A 127 type design system 10
4.1 Initial deflection 10
4.2 Long-term deflection calculated using an ATV-A 127 type design system 16

5 Soil parameters, strain coefficients and shape factors for flexural strain calculations 17
5.1 For equations used in ATV-A 127 type design systems 17
5.2 Shape factor, Df 19

6 Influence of soil moduli and pipe stiffness on pipe buckling calculations using ATV-A 127 type design systems 22
6.1 Elastic buckling under internal negative pressure for depths of cover over 1 m 22
6.2 Long-term buckling under sustained external load 23
6.3 Value for SO 23

7 Parameters for rerounding and combined loading calculations 23
7.1 Rerounding 23
7.2 Combined effects of internal pressure and external bending loads 23

8 Traffic loads 24
8.1 General 24
8.2 Influence on allowable initial deflection 24
8.3 Soil pressure from traffic loads 24

9 Influence of sheeting 24

10 Safety factors for gravity pipes and pressure pipes 25
10.1 Gravity pipes 25
10.2 Pressure pipes 27
10.3 Safety factors in buckling calculations 29

Annex A (informative) Soil parameters 30

Annex B (informative) Determination of concentration factors used in ATV-A 127 42

Annex C (informative) Loading coefficients used in ATV-A 127 43

Annex D (informative) Horizontal bedding correction factors 44

Annex E (informative) Selection of long-term stiffness 46

Annex F (informative) Partly residual soil friction used in ATV-A 127 type calculation systems 48

Annex G (informative) Application limits for GRP pressure pipes installed underground 50

Bibliography 63