

ISO/TR 10465-3:2007-09 (E)

Underground installation of flexible glass-reinforced pipes based on unsaturated polyester resin (GRP-UP) - Part 3: Installation parameters and application limits

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Symbols and abbreviated terms	1
4	Parameters for deflection calculations when using an ATV-A 127 type design system	10
4.1	Initial deflection	10
4.2	Long-term deflection calculated using an ATV-A 127 type design system	16
5	Soil parameters, strain coefficients and shape factors for flexural strain calculations	17
5.1	For equations used in ATV-A 127 type design systems	17
5.2	Shape factor, Df	19
6	Influence of soil moduli and pipe stiffness on pipe buckling calculations using ATV-A 127 type design systems	22
6.1	Elastic buckling under internal negative pressure for depths of cover over 1 m	22
6.2	Long-term buckling under sustained external load	23
6.3	Value for SO	23
7	Parameters for rerounding and combined loading calculations	23
7.1	Rerounding	23
7.2	Combined effects of internal pressure and external bending loads	23
8	Traffic loads	24
8.1	General	24
8.2	Influence on allowable initial deflection	24
8.3	Soil pressure from traffic loads	24
9	Influence of sheeting	24
10	Safety factors for gravity pipes and pressure pipes	25
10.1	Gravity pipes	25
10.2	Pressure pipes	27
10.3	Safety factors in buckling calculations	29
Annex A (informative)	Soil parameters	30
Annex B (informative)	Determination of concentration factors used in ATV-A 127	42
Annex C (informative)	Loading coefficients used in ATV-A 127	43
Annex D (informative)	Horizontal bedding correction factors	44
Annex E (informative)	Selection of long-term stiffness	46
Annex F (informative)	Partly residual soil friction used in ATV-A 127 type calculation systems	48
Annex G (informative)	Application limits for GRP pressure pipes installed underground	50
Bibliography		63