

# ISO 22621-3:2007-11 (E)

## Plastics piping systems for the supply of gaseous fuels for maximum operating pressures up to and including 2 MPa (20 bar) - Polyamide (PA) - Part 3: Fittings

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1 <b>Scope</b> .....		1
2 <b>Normative references</b> .....		1
3 <b>Terms, definitions, symbols and abbreviated terms</b> .....		2
4 <b>Material</b> .....		3
5 <b>General characteristics</b> .....		4
6 <b>Geometrical characteristics</b> .....		5
7 <b>Mechanical characteristics</b> .....		10
8 <b>Physical characteristics</b> .....		12
9 <b>Chemical resistance of fittings in contact with chemicals</b> .....		12
10 <b>Marking</b> .....		12
11 <b>Packaging</b> .....		13
<b>Annex A (informative) Examples of typical terminal connections for electrofusion fittings</b> .....		14
<b>Annex B (normative) Short-term pressure test method</b> .....		16
<b>Annex C (normative) Tensile test fitting/pipe assemblies</b> .....		18
<b>Annex D (normative) Tear test for saddles assemblies</b> .....		19
<b>Bibliography</b> .....		22