DIN 8077:2008-09 (E)

Polypropylene (PP) pipes - PP-H, PP-B, PP-R, PP-RCT - Dimensions

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Safety factors 6

5 Dimensions and designation 7
5.1 General 7
5.2 Outside diameters, wall thicknesses, S/SDR series and masses 8
5.3 Tolerances on mean outside diameters and out-of-roundness 11
5.4 Tolerances on wall thicknesses 13

6 Allowable operating pressures 15
6.1 Allowable operating pressures for pipes conveying water 15
6.2 Allowable operating pressures for pipes conveying other fluids 15

7 Form supplied 31

8 Marking 32

Annex A (informative) Explanatory notes 33

Annex B (informative) Bibliography 34

Figures Figure 1 -- Outside diameter and wall thickness 7

Tables Table 1 -- Safety factor SF as a function of the temperature 6

Table 2 -- Outside diameters, wall thicknesses, S/SDR series and masses 8

Table 3 -- Tolerances on mean outside diameters and out-of-roundness 11

Table 4 -- Tolerances on wall thicknesses 13

Table 5 -- Allowable operating pressures for PP-H pipes conveying water, safety factor (SF) = 1,6 - 1,25 (temperature-dependent) 16

Table 6 -- Allowable operating pressures for PP-H pipes conveying water, safety factor (SF) = 1,7 ...18

Table 7 -- Allowable operating pressures for PP-B pipes conveying water, safety factor (SF) = 1,25 .20

Table 8 -- Allowable operating pressures for PP-B pipes conveying water, safety factor (SF) = 1,5 ...22

Table 9 -- Allowable operating pressures for PP-R pipes conveying water, safety factor (SF) = 1,25 .24

Table 10 -- Allowable operating pressures for PP-R pipes conveying water, safety factor (SF) = 1,5 .26

Table 11 -- Allowable operating pressures for PP-RCT pipes conveying water, safety factor (SF) = 1,25 28

Table 12 -- Allowable operating pressures for PP-RCT pipes conveying water, safety factor (SF) = 1,5 30

Table 13 -- Tolerances on nominal lengths 31