

DIN 8077:2008-09 (E)

Polypropylene (PP) pipes - PP-H, PP-B, PP-R, PP-RCT - Dimensions

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Safety factors	6
5	Dimensions and designation	7
5.1	General	7
5.2	Outside diameters, wall thicknesses, S/SDR series and masses	8
5.3	Tolerances on mean outside diameters and out-of-roundness	11
5.4	Tolerances on wall thicknesses	13
6	Allowable operating pressures	15
6.1	Allowable operating pressures for pipes conveying water	15
6.2	Allowable operating pressures for pipes conveying other fluids	15
7	Form supplied	31
8	Marking	32
Annex A (informative) Explanatory notes		33
Annex B (informative) Bibliography		34
Figures Figure 1 -- Outside diameter and wall thickness		7
Tables Table 1 -- Safety factor SF as a function of the temperature		6
Table 2 -- Outside diameters, wall thicknesses, S/SDR series and masses		8
Table 3 -- Tolerances on mean outside diameters and out-of-roundness		11
Table 4 -- Tolerances on wall thicknesses		13
Table 5 -- Allowable operating pressures for PP-H pipes conveying water, safety factor (SF) = 1,6 - 1,25 (temperature-dependent)		16
Table 6 -- Allowable operating pressures for PP-H pipes conveying water, safety factor (SF) = 1,7 ...		18
Table 7 -- Allowable operating pressures for PP-B pipes conveying water, safety factor (SF) = 1,25 .		20
Table 8 -- Allowable operating pressures for PP-B pipes conveying water, safety factor (SF) = 1,5 ...		22
Table 9 -- Allowable operating pressures for PP-R pipes conveying water, safety factor (SF) = 1,25 .		24
Table 10 -- Allowable operating pressures for PP-R pipes conveying water, safety factor (SF) = 1,5 .		26

Table 11 -- Allowable operating pressures for PP-RCT pipes conveying water, safety factor (SF) = 1,25	28
Table 12 -- Allowable operating pressures for PP-RCT pipes conveying water, safety factor (SF) = 1,5	30
Table 13 -- Tolerances on nominal lengths	31