

DIN 16834:2009-10 (E)

Pipes of raised-temperature-resistance polyethylene (PE-RT) - PE-RT Type I and PE-RT Type II - Dimensions

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Safety factors	5
5	Dimensions and designation	5
5.1	General	5
5.2	Outside diameters, wall thicknesses, S/SDR series and masses	6
5.3	Tolerances on mean outside diameter and out-of-roundness	7
5.4	Tolerances on wall thickness	8
6	Allowable working pressures	9
6.1	Allowable working pressures for pipes conveying water	9
6.2	Allowable working pressures for pipes conveying other liquids	9
7	Form supplied	14
8	Marking	14
8.1	General	14
8.2	Minimum marking information	14
Annex A (informative)	Explanatory notes	15
Bibliography		16
Figure	Figure 1 -- Outside diameter and wall thickness	5
Tables	Table 1 -- Outside diameters, wall thicknesses, S/SDR series and masses	6
	Table 2 -- Tolerances on mean outside diameter and out-of roundness	7
	Table 3 -- Tolerances on wall thickness	8
	Table 4 -- Allowable working pressures for PE-RT type I pipes onveying water, with SF = 1,25	10
	Table 5 -- Allowable working pressures for PE-RT type I pipes conveying water, with SF = 1,5	11
	Table 6 -- Allowable working pressures for PE-RT type II pipes conveying water, with SF = 1,25	12
	Table 7 -- Allowable working pressures for PE-RT type II pipes conveying water, with SF = 1,5	13
	Table 8 -- Tolerances for pipe lengths	14