DIN 8080:2009-10 (E)

Chlorinated polyvinyl chloride (PVC-C) pipes - General quality requirements, testing

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Material (moulding material) 5
4.1 General 5
4.2 Demonstrating long-term hydrostatic strength 5

5 Requirements 7
5.1 Form supplied and surface quality 7
5.2 Dimensions, tolerances and out-of-roundness 7
5.3 Strength characteristics determined by long-term hydrostatic strength testing 7
5.4 Impact strength 7
5.4.1 General 7
5.4.2 Impact strength when testing as in 6.4.2 8
5.4.3 Resistance to external blows 8
5.5 Heat reversion 8
5.6 Vicat softening temperature 8

6 Testing 8
6.1 Surface quality 8
6.2 Dimensions and out-of-roundness 8
6.3 Strength characteristics determined by long-term hydrostatic strength testing 8
6.4 Impact strength 10
6.4.1 General 10
6.4.2 Impact strength testing 10
6.4.3 Resistance to external blows 11
6.5 Heat reversion 12
6.6 Vicat softening temperature 13
6.7 Inspection documents 13

Annex A (informative) Explanatory notes 14

Bibliography 15

Figures Figure 1 -- Reference lines for long-term hydrostatic strength (time-to-failure curves) for PVC-C pipes 6

Figure 2 -- Test piece for long-term hydrostatic strength test 9

Tables Table 1 -- Test conditions for long-term hydrostatic strength testing 7

Table 2 -- Test conditions for impact test 10

Table 3 -- Striker 11

Table 4 -- Masses and fall heights for pipe series SDR 9 to SDR 26 at level M 11

Table 5 -- Masses and fall heights for pipe series SDR 34,4 at level H 12

Table 6 -- Test conditions for heat reversion test 13

Table A.1 -- PVC-C properties (guideline values) 14