

# DIN 8080:2009-10 (E)

## Chlorinated polyvinyl chloride (PVC-C) pipes - General quality requirements, testing

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| Foreword .....   |  | 3           |
| <b>1</b>   | <b>Scope .....</b>   | <b>4</b>    |
| <b>2</b>   | <b>Normative references .....</b>  | <b>4</b>    |
| <b>3</b>   | <b>Terms and definitions .....</b>   | <b>4</b>    |
| <b>4</b>   | <b>Material (moulding material) .....</b>  | <b>5</b>    |
| <b>4.1</b>   | <b>General .....</b>   | <b>5</b>    |
| <b>4.2</b>   | <b>Demonstrating long-term hydrostatic strength .....</b>  | <b>5</b>    |
| <b>5</b>   | <b>Requirements .....</b>  | <b>7</b>    |
| <b>5.1</b>   | <b>Form supplied and surface quality .....</b>   | <b>7</b>    |
| <b>5.2</b>   | <b>Dimensions, tolerances and out-of-roundness .....</b>   | <b>7</b>    |
| <b>5.3</b>   | <b>Strength characteristics determined by long-term hydrostatic strength testing .....</b>                           | <b>7</b>    |
| <b>5.4</b>   | <b>Impact strength .....</b>   | <b>7</b>    |
| <b>5.4.1</b>   | <b>General .....</b>   | <b>7</b>    |
| <b>5.4.2</b>   | <b>Impact strength when testing as in 6.4.2 .....</b>  | <b>8</b>    |
| <b>5.4.3</b>   | <b>Resistance to external blows .....</b>  | <b>8</b>    |
| <b>5.5</b>   | <b>Heat reversion .....</b>  | <b>8</b>    |
| <b>5.6</b>   | <b>Vicat softening temperature .....</b>   | <b>8</b>    |
| <b>6</b>   | <b>Testing .....</b>   | <b>8</b>    |
| <b>6.1</b>   | <b>Surface quality .....</b>   | <b>8</b>    |
| <b>6.2</b>   | <b>Dimensions and out-of-roundness .....</b>   | <b>8</b>    |
| <b>6.3</b>   | <b>Strength characteristics determined by long-term hydrostatic strength testing .....</b>                           | <b>8</b>    |
| <b>6.4</b>   | <b>Impact strength .....</b>   | <b>10</b>   |
| <b>6.4.1</b>   | <b>General .....</b>   | <b>10</b>   |
| <b>6.4.2</b>   | <b>Impact strength testing .....</b>   | <b>10</b>   |
| <b>6.4.3</b>   | <b>Resistance to external blows .....</b>  | <b>11</b>   |
| <b>6.5</b>   | <b>Heat reversion .....</b>  | <b>12</b>   |
| <b>6.6</b>   | <b>Vicat softening temperature .....</b>   | <b>13</b>   |
| <b>6.7</b>   | <b>Inspection documents .....</b>  | <b>13</b>   |
| <b>Annex A (informative)</b>   | <b>Explanatory notes .....</b>   | <b>14</b>   |
| <b>Bibliography .....</b>  |  | <b>15</b>   |
| <b>Figures</b>   | <b>Figure 1 -- Reference lines for long-term hydrostatic strength (time-to-failure curves) for PVC-C pipes .....</b> | <b>6</b>    |
| <b>Figure 2 -- Test piece for long-term hydrostatic strength test .....</b>                |  | <b>9</b>    |
| <b>Tables</b>  | <b>Table 1 -- Test conditions for long-term hydrostatic strength testing .....</b>                                   | <b>7</b>    |
| <b>Table 2 -- Test conditions for impact test .....</b>                                    |  | <b>10</b>   |
| <b>Table 3 -- Striker .....</b>  |  | <b>11</b>   |
| <b>Table 4 -- Masses and fall heights for pipe series SDR 9 to SDR 26 at level M .....</b> |  | <b>11</b>   |

|   |           |
|---|-----------|
| <b>Table 5 -- Masses and fall heights for pipe series SDR 34,4 at level H .....</b> | <b>12</b> |
| <b>Table 6 -- Test conditions for heat reversion test .....</b>                     | <b>13</b> |
| <b>Table A.1 -- PVC-C properties (guideline values) .....</b>                       | <b>14</b> |