DIN 16833:2009-09 (E)

Pipes of raised-temperature-resistance polyethlyene (PE-RT) - PE-RT Type I and PE-RT Type II - General quality requirements, testing

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Material (moulding material) 5
4.1 General 5
4.2 Demonstrating long-term hydrostatic strength 5

5 Requirements 7
5.1 Form supplied 7
5.2 Surface quality 8
5.3 Dimensions and tolerances 8
5.4 Strength characteristics determined by long-term hydrostatic strength testing 8
5.5 Demonstrating thermal stability by means of long-term hydrostatic strength testing 8
5.6 Heat reversion 8

6 Testing 9
6.1 Surface quality 9
6.2 Dimensions 9
6.3 Out-of-roundness 9
6.4 Strength characteristics determined by long-term hydrostatic strength testing 9
6.5 Heat reversion 10
6.6 Inspection documents 10

Annex A (informative) Explanatory notes 11

Bibliography 13

Figures Figure 1 -- Reference lines for long-term hydrostatic strength (time-to-failure curves) for pipes of polyethylene of raised temperature resistance PE-RT type I 6

Figure 2 -- Reference lines for long-term hydrostatic strength (time-to-failure curves) for pipes of polyethylene of raised temperature resistance PE-RT type II 7

Figure 3 -- Test piece for long-term hydrostatic strength test 9

Tables Table 1 -- Test conditions for long-term hydrostatic strength testing 8

Table 2 -- Thermal stability demonstrated by means of long-term hydrostatic strength testing 8

Table 3 -- Test conditions for heat reversion test 10

Table A.1 -- PE-RT properties (guideline values) 12