

ISO 25217:2009-05 (E)

Adhesives - Determination of the mode 1 adhesive fracture energy of structural adhesive joints using double cantilever beam and tapered double cantilever beam specimens

Contents	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Symbols and abbreviated terms	1
4 Principle	3
5 Apparatus	3
6 Specimens	3
6.1 Number of specimens	3
6.2 Conditioning	4
6.3 Manufacture of adhesive joint specimens	4
6.4 Measurement of specimen dimensions	6
6.4.1 DCB substrates	6
6.4.2 TDCB substrates	6
6.4.3 DCB and TDCB substrates	6
6.5 Preparation of specimens	7
7 Procedure	7
7.1 Test set-up and data recording	7
7.2 Initial loading (the precracking stage)	7
7.3 Re-loading: Testing from the mode I precrack	8
7.4 Measurement of machine compliance	9
8 Data analysis	9
8.1 Determination of the raw data from the load-displacement trace	9
8.1.1 General	9
8.1.2 Initiation values	9
8.1.3 Propagation values	10
8.2 Determination of GIC	10
8.2.1 General	10
8.2.2 Double cantilever beam (DCB)	10
8.2.3 Tapered double cantilever beam (TDCB)	12
9 Test report	13
9.1 Test report for the DCB test	13
9.2 Test report for the TDCB test	14
Annex A (informative) Measurement of test system compliance	16
Annex B (normative) Procedure to follow when unstable or "stick-slip" crack growth is observed during the fracture test	18
Annex C (normative) Procedure to detect the occurrence of plastic deformation during a DCB or TDCB adhesive joint test	19
Annex D (informative) Summary of background theory	20
Bibliography	24