

ISO 25217:2009-05 (E)

Adhesives - Determination of the mode 1 adhesive fracture energy of structural adhesive joints using double cantilever beam and tapered double cantilever beam specimens

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Symbols and abbreviated terms | 1 |
| 4 | Principle | 3 |
| 5 | Apparatus | 3 |
| 6 | Specimens | 3 |
| 6.1 | Number of specimens | 3 |
| 6.2 | Conditioning | 4 |
| 6.3 | Manufacture of adhesive joint specimens | 4 |
| 6.4 | Measurement of specimen dimensions | 6 |
| 6.4.1 | DCB substrates | 6 |
| 6.4.2 | TDCB substrates | 6 |
| 6.4.3 | DCB and TDCB substrates | 6 |
| 6.5 | Preparation of specimens | 7 |
| 7 | Procedure | 7 |
| 7.1 | Test set-up and data recording | 7 |
| 7.2 | Initial loading (the precracking stage) | 7 |
| 7.3 | Re-loading: Testing from the mode I precrack | 8 |
| 7.4 | Measurement of machine compliance | 9 |
| 8 | Data analysis | 9 |
| 8.1 | Determination of the raw data from the load-displacement trace | 9 |
| 8.1.1 | General | 9 |
| 8.1.2 | Initiation values | 9 |
| 8.1.3 | Propagation values | 10 |
| 8.2 | Determination of GIC | 10 |
| 8.2.1 | General | 10 |
| 8.2.2 | Double cantilever beam (DCB) | 10 |
| 8.2.3 | Tapered double cantilever beam (TDCB) | 12 |
| 9 | Test report | 13 |
| 9.1 | Test report for the DCB test | 13 |
| 9.2 | Test report for the TDCB test | 14 |
| Annex A (informative) Measurement of test system compliance | | 16 |
| Annex B (normative) Procedure to follow when unstable or "stick-slip" crack growth is observed during the fracture test | | 18 |
| Annex C (normative) Procedure to detect the occurrence of plastic deformation during a DCB or TDCB adhesive joint test | | 19 |
| Annex D (informative) Summary of background theory | | 20 |
| Bibliography | | 24 |