

# ISO 25217:2009-05 (E)

## Adhesives - Determination of the mode 1 adhesive fracture energy of structural adhesive joints using double cantilever beam and tapered double cantilever beam specimens

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
1	Scope .....	1
2	Normative references .....	1
3	Symbols and abbreviated terms .....	1
4	Principle .....	3
5	Apparatus .....	3
6	Specimens .....	3
6.1	Number of specimens .....	3
6.2	Conditioning .....	4
6.3	Manufacture of adhesive joint specimens .....	4
6.4	Measurement of specimen dimensions .....	6
6.4.1	DCB substrates .....	6
6.4.2	TDCB substrates .....	6
6.4.3	DCB and TDCB substrates .....	6
6.5	Preparation of specimens .....	7
7	Procedure .....	7
7.1	Test set-up and data recording .....	7
7.2	Initial loading (the precracking stage) .....	7
7.3	Re-loading: Testing from the mode I precrack .....	8
7.4	Measurement of machine compliance .....	9
8	Data analysis .....	9
8.1	Determination of the raw data from the load-displacement trace .....	9
8.1.1	General .....	9
8.1.2	Initiation values .....	9
8.1.3	Propagation values .....	10
8.2	Determination of GIC .....	10
8.2.1	General .....	10
8.2.2	Double cantilever beam (DCB) .....	10
8.2.3	Tapered double cantilever beam (TDCB) .....	12
9	Test report .....	13
9.1	Test report for the DCB test .....	13
9.2	Test report for the TDCB test .....	14
Annex A (informative) Measurement of test system compliance .....		16
Annex B (normative) Procedure to follow when unstable or "stick-slip" crack growth is observed during the fracture test .....		18
Annex C (normative) Procedure to detect the occurrence of plastic deformation during a DCB or TDCB adhesive joint test .....		19
Annex D (informative) Summary of background theory .....		20
Bibliography .....		24