ISO 25217:2009-05 (E)

Adhesives - Determination of the mode 1 adhesive fracture energy of structural adhesive joints using double cantilever beam and tapered double cantilever beam specimens

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Symbols and abbreviated terms 1

4 Principle 3

5 Apparatus 3

6 Specimens 3
6.1 Number of specimens 3
6.2 Conditioning 4
6.3 Manufacture of adhesive joint specimens 4
6.4 Measurement of specimen dimensions 6
6.4.1 DCB substrates 6
6.4.2 TDCB substrates 6
6.4.3 DCB and TDCB substrates 6
6.5 Preparation of specimens 7

7 Procedure 7
7.1 Test set-up and data recording 7
7.2 Initial loading (the precracking stage) 7
7.3 Re-loading: Testing from the mode I precrack 8
7.4 Measurement of machine compliance 9

8 Data analysis 9
8.1 Determination of the raw data from the load-displacement trace 9
8.1.1 General 9
8.1.2 Initiation values 9
8.1.3 Propagation values 10
8.2 Determination of GIC 10
8.2.1 General 10
8.2.2 Double cantilever beam (DCB) 10
8.2.3 Tapered double cantilever beam (TDCB) 12

9 Test report 13
9.1 Test report for the DCB test 13
9.2 Test report for the TDCB test 14

Annex A (informative) Measurement of test system compliance 16

Annex B (normative) Procedure to follow when unstable or "stick-slip" crack growth is observed during the fracture test 18

Annex C (normative) Procedure to detect the occurrence of plastic deformation during a DCB or TDCB adhesive joint test 19

Annex D (informative) Summary of background theory 20

Bibliography 24