

# DIN EN ISO 1452-4:2010-04 (E)

Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure - Unplasticized poly(vinyl chloride) (PVC-U) - Part 4: Valves (ISO 1452-4:2009)

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | 3           |
| Introduction ..... |  | 4           |
| <b>1</b>           | <b>Scope .....</b>   | <b>5</b>    |
| <b>2</b>           | <b>Normative references .....</b>  | <b>6</b>    |
| <b>3</b>           | <b>Terms, definitions, symbols and abbreviated terms .....</b>                       | <b>7</b>    |
| <b>4</b>           | <b>Material .....</b>  | <b>7</b>    |
| <b>4.1</b>         | <b>Valve bodies .....</b>  | <b>7</b>    |
| <b>4.2</b>         | <b>Density .....</b>   | <b>7</b>    |
| <b>4.3</b>         | <b>MRS-value .....</b>   | <b>7</b>    |
| <b>4.4</b>         | <b>Additional components .....</b>   | <b>7</b>    |
| <b>5</b>           | <b>General characteristics .....</b>   | <b>7</b>    |
| <b>5.1</b>         | <b>Appearance .....</b>  | <b>7</b>    |
| <b>5.2</b>         | <b>Colour .....</b>  | <b>7</b>    |
| <b>5.3</b>         | <b>Opacity .....</b>   | <b>7</b>    |
| <b>6</b>           | <b>Geometrical characteristics .....</b>   | <b>8</b>    |
| <b>6.1</b>         | <b>Measurement of dimensions .....</b>   | <b>8</b>    |
| <b>6.2</b>         | <b>Nominal diameters .....</b>   | <b>8</b>    |
| <b>6.3</b>         | <b>Valves dimensions .....</b>   | <b>8</b>    |
| <b>7</b>           | <b>Classification and operating conditions .....</b>                                 | <b>8</b>    |
| <b>7.1</b>         | <b>Classification .....</b>  | <b>8</b>    |
| <b>7.2</b>         | <b>Determination of the allowable operating pressure for water up to 45 °C .....</b> | <b>8</b>    |
| <b>8</b>           | <b>Mechanical characteristics .....</b>  | <b>9</b>    |
| <b>8.1</b>         | <b>Resistance of valve bodies to internal pressure .....</b>                         | <b>9</b>    |
| <b>8.2</b>         | <b>Crushing test .....</b>   | <b>9</b>    |
| <b>8.3</b>         | <b>Durability .....</b>  | <b>9</b>    |
| <b>8.4</b>         | <b>Functional properties .....</b>   | <b>9</b>    |
| <b>9</b>           | <b>Physical characteristics .....</b>  | <b>9</b>    |
| <b>10</b>          | <b>Chemical characteristics .....</b>  | <b>10</b>   |
| <b>11</b>          | <b>Sealing rings .....</b>   | <b>10</b>   |
| <b>12</b>          | <b>Adhesives .....</b>   | <b>10</b>   |
| <b>13</b>          | <b>Performance requirements .....</b>  | <b>11</b>   |
| <b>14</b>          | <b>Marking .....</b>   | <b>11</b>   |
| <b>14.1</b>        | <b>General .....</b>   | <b>11</b>   |
| <b>14.2</b>        | <b>Minimum required marking .....</b>  | <b>11</b>   |

|             |  |           |
|-------------|--|-----------|
| <b>14.3</b> | <b>Additional marking .....</b>                              | <b>12</b> |
|             | <b>Annex A (normative) Imperial(inch)-sized valves .....</b> | <b>13</b> |
|             | <b>Bibliography .....</b>                                    | <b>15</b> |