

ISO 18352:2009-08 (E)

Carbon-fibre-reinforced plastics - Determination of compression-after-impact properties at a specified impact-energy level

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Principle | 3 |
| 5 | Conditioning of specimens and test environment | 4 |
| 5.1 | Standard conditioning procedure for specimens | 4 |
| 5.2 | Environmental test chamber for impact and compression tests | 4 |
| 6 | Test apparatus | 4 |
| 6.1 | General | 4 |
| 6.2 | Impact facility | 4 |
| 6.3 | Support fixture for specimen | 4 |
| 6.4 | Non-destructive testing instrument | 6 |
| 6.5 | Compression-testing machine | 6 |
| 6.6 | Compression-loading fixture | 6 |
| 6.7 | Measuring apparatus | 7 |
| 6.8 | Strain gauges | 8 |
| 7 | Specimens | 8 |
| 7.1 | Dimensions | 8 |
| 7.2 | Specimen preparation | 9 |
| 7.3 | Number of specimens | 10 |
| 8 | Procedure | 10 |
| 8.1 | Specimen conditioning | 10 |
| 8.2 | Measurement of specimen dimensions | 10 |
| 8.3 | Impact test | 10 |
| 8.4 | Non-destructive testing (NDT) | 11 |
| 8.5 | Inspection of specimens | 11 |
| 8.6 | Compression test | 11 |
| 9 | Validation | 13 |
| 10 | Calculation of results | 14 |
| 10.1 | CAI strength | 14 |
| 10.2 | CAI modulus | 15 |
| 10.3 | Maximum CAI strain | 15 |
| 10.4 | Rounding the results | 15 |
| 10.5 | Standard deviation and coefficient of variation | 15 |
| 11 | Test report | 16 |
| Annex A (normative) Detailed drawings of the components of the compression-loading fixture | | 17 |
| Bibliography | | 20 |