

DIN EN 15836-2:2010-11 (E)

Plastics - Plasticized poly(vinyl chloride) (PVC-P) membranes for inground swimming pools - Part 2: Reinforced membranes of nominal thickness equal to or greater than 1,5 mm

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms, definitions, symbols and abbreviations	6
3.1	Terms and definitions	6
3.2	Symbols	6
3.3	Abbreviations	6
4	Sampling and conditioning	6
4.1	Sampling	6
4.2	Conditioning of test pieces	6
5	Membrane composition	7
5.1	Characteristics of the membrane	7
5.2	Heavy metals and other dangerous substances	7
5.3	Environmental aspects	7
6	Visual characteristics	7
6.1	Appearance	7
6.2	Colour (plain coloured membranes)	8
6.3	Abrasion resistance (printed and/or coated reinforced membranes)	8
6.3.1	Test method	8
6.3.2	Requirement	9
7	Physico-chemical characteristic	9
8	Dimensional characteristics	9
9	Mechanical characteristics	10
10	Characteristics for durability	11
11	Storage conditions	11
12	Installation, refurbishment, exploitation and maintenance	12
13	Designation and marking	12
13.1	Designation	12
13.2	Marking	12
Annex A (normative) Determination of the contents of CaCO₃, heavy metals and other elements		13
Annex B (normative) Testing of slip resistance		14
B.1	Principle	14
B.2	Testing person	14

B.3	Test rig	14
B.4	Test liquid	14
B.5	Test specimen	14
B.6	Test procedure	14
B.7	Evaluation	15
B.8	Classification	15
B.9	Test report	15
Annex C (normative) Assessment of chlorine resistance		16
C.1	Principle	16
C.2	Test liquid	16
C.3	Apparatus	16
C.4	Test pieces	16
C.5	Procedure	16
C.6	Test report	17
Annex D (normative) Assessment of the resistance to staining agents		18
D.1	Principle	18
D.2	Staining agents	18
D.3	Apparatus	18
D.4	Test specimens	18
D.5	Procedure	18
D.6	Expression of results	19
D.7	Test report	19
Bibliography		20