

DIN EN 13245-1:2010-11 (E)

Plastics - Unplasticized poly(vinyl chloride) (PVC-U) profiles for building applications - Part 1: Designation of PVC-U profiles

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	5
4	Designation of PVC-U profiles	6
5	Codification system for Data block 3 to Data block 5	7
5.1	Vicat softening temperature (Data block 3)	7
5.2	Modulus of elasticity in flexure (Data block 3)	7
5.3	Nominal linear mass (Data block 4)	8
5.4	Heat reversion at 100 °C (Data block 4)	8
5.5	Impact resistance (Data block 4)	8
5.6	Durability (Data block 5)	9
6	Required characteristics for Type 3 and Type 4 profiles	13
6.1	Resistance to cross cut (only for Type 4 profiles)	13
6.2	Thermal resistance (only for Type 3 and Type 4 profiles)	13
6.3	Water vapour resistance (only for Type 3 and Type 4 profiles, intended to be used for inside building applications)	13
6.4	Peel strength (only for Type 3 profiles)	13
7	Optional characteristics	13
7.1	Resistance to staining	13
7.2	Appearance and finishing of the coating (only for Type 3 and Type 4 profiles)	14
8	Example of the designation of a PVC-U profile	14
9	Use of reprocessable and recyclable material	15
Annex A (normative) Determination of the linear mass		16
A.1	Apparatus	16
A.2	Test specimens	16
A.3	Procedure	16
A.4	Calculation and expression of results	16
Annex B (normative) Determination of the impact resistance		17
B.1	Principle	17
B.2	Apparatus	17
B.3	Test specimens	17
B.4	Conditioning	18
B.5	Procedure	18
B.6	Expression of results	19
Annex C (normative) Determination of peel strength		20

C.1	Principle	20
C.2	Apparatus	20
C.3	Preparation of test pieces	21
C.4	Conditioning	21
C.5	Procedure	21
C.6	Test report	22
Bibliography		23