

ISO 10580:2010-04 (E)

Resilient, textile and laminate floor coverings - Test method for volatile organic compound (VOC) emissions

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	4
5	Apparatus	4
6	Sampling the product and transport and storage of sample	4
6.1	Sampling	4
6.2	Sample packaging and transport	5
6.3	Sample description	5
6.4	Storage of the sample prior to starting the testing	6
7	Preparation of test specimens	6
7.1	Specimens from rolls	6
7.2	Samples of rigid products such as tiles and planks	6
8	Emission test chamber system	7
8.1	General	7
8.2	Emission test chamber description	7
8.3	Air supply and mixing facilities	7
8.4	Airtightness	7
8.5	Air sampling manifold	7
8.6	Recovery and sink effects	8
9	Test conditions	8
9.1	Temperature and relative air humidity	8
9.2	Temperature and relative-air-humidity control systems	8
9.3	Supply-air quality and background concentration	9
9.4	Air velocity	9
9.5	Loading factor and air change rate	9
9.6	Air change rate in the emission test chamber	9
9.7	Emission test chamber airtightness	9
9.8	Efficiency of the internal emission-test-chamber air mixing	9
10	Preparation of emission test chamber	10
11	Test procedure	10
11.1	Test conditions in the emission test chamber	10
11.2	Background concentrations	10
11.3	Test specimen location in the emission test chamber	10
11.4	Time for measurements of test-chamber air concentration	10
11.5	Air sampling	10

12	Analysis of the air samples	12
12.1	Analysis of VOC	12
12.2	Analysis of formaldehyde and carbonyl compounds	12
13	Calculation of vapour concentrations and area-specific emission rates	12
14	Performance characteristics	12
15	Test report	13
	Annex A (informative) General description of an emission test chamber	14
	Annex B (informative) Evaluation systems	15
	Bibliography	20