ISO 11299-3:2011-09 (E)

Plastics piping systems for renovation of underground gas supply networks - Part 3: Lining with close-fit pipes

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1
3.1 General 1
3.2 Techniques 2
3.3 Characteristics 2
3.4 Materials 2
3.5 Product stages 2
3.6 Service conditions 2
3.7 Joints 2

4 Symbols and abbreviated terms 3
4.1 Symbols 3
4.2 Abbreviated terms 3

5 Pipes at the "M" stage 3
5.1 Materials 3
5.2 General characteristics 4
5.3 Material characteristics 4
5.4 Geometric characteristics 4
5.5 Mechanical characteristics 4
5.6 Physical characteristics 5
5.7 Jointing 5
5.8 Marking 5

6 Fittings at the "M" stage 5

7 Ancillary components 5

8 Fitness for purpose of the installed lining system at the "I" stage 5
8.1 Materials 5
8.2 General characteristics 5
8.3 Material characteristics 5
8.4 Geometric characteristics 6
8.5 Mechanical characteristics 6
8.6 Physical characteristics 7
8.7 Additional characteristics 7
8.8 Sampling 8

9 Installation practice 8
9.1 Preparatory work 8
9.2 Storage, handling and transport of pipes and fittings 8
9.3 Equipment 8
9.4 Installation 9
9.5 Process-related inspection and testing 10

Annex A (normative) Factory-folded heat-reverted polyethylene (PE) pipe -- Determination of memory ability 11

Bibliography 13