

DIN EN ISO 10580:2012-04 (E)

Resilient, textile and laminate floor coverings - Test method for volatile organic compound (VOC) emissions (ISO 10580:2010)

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 6 |
| 4 | Symbols and abbreviated terms | 8 |
| 5 | Apparatus | 8 |
| 6 | Sampling the product and transport and storage of sample | 8 |
| 6.1 | Sampling | 8 |
| 6.2 | Sample packaging and transport | 9 |
| 6.3 | Sample description | 9 |
| 6.4 | Storage of the sample prior to starting the testing | 10 |
| 7 | Preparation of test specimens | 10 |
| 7.1 | Specimens from rolls | 10 |
| 7.2 | Samples of rigid products such as tiles and planks | 10 |
| 8 | Emission test chamber system | 11 |
| 8.1 | General | 11 |
| 8.2 | Emission test chamber description | 11 |
| 8.3 | Air supply and mixing facilities | 11 |
| 8.4 | Airtightness | 11 |
| 8.5 | Air sampling manifold | 11 |
| 8.6 | Recovery and sink effects | 12 |
| 9 | Test conditions | 12 |
| 9.1 | Temperature and relative air humidity | 12 |
| 9.2 | Temperature and relative-air-humidity control systems | 12 |
| 9.3 | Supply-air quality and background concentration | 13 |
| 9.4 | Air velocity | 13 |
| 9.5 | Loading factor and air change rate | 13 |
| 9.6 | Air change rate in the emission test chamber | 13 |
| 9.7 | Emission test chamber airtightness | 13 |
| 9.8 | Efficiency of the internal emission-test-chamber air mixing | 13 |
| 10 | Preparation of emission test chamber | 14 |
| 11 | Test procedure | 14 |
| 11.1 | Test conditions in the emission test chamber | 14 |
| 11.2 | Background concentrations | 14 |
| 11.3 | Test specimen location in the emission test chamber | 14 |
| 11.4 | Time for measurements of test-chamber air concentration | 14 |
| 11.5 | Air sampling | 14 |

| | | |
|-------------|--|-----------|
| 12 | Analysis of the air samples | 16 |
| 12.1 | Analysis of VOC | 16 |
| 12.2 | Analysis of formaldehyde and carbonyl compounds | 16 |
| 13 | Calculation of vapour concentrations and area-specific emission rates | 16 |
| 14 | Performance characteristics | 16 |
| 15 | Test report | 17 |
| | Annex A (informative) General description of an emission test chamber | 18 |
| | Annex B (informative) Evaluation systems | 19 |
| | Bibliography | 24 |