DIN EN ISO 307:2013-08 (E)

Plastics - Polyamides - Determination of viscosity number (ISO 307:2007 + Amd 1:2013) (includes Amendment :2013)

Contents

Page

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 6

4 Principle 7

5 Reagents and materials 7
5.1 Solvents and reagents 7
5.2 Cleaning liquids 8

6 Apparatus 8

7 Preparation of test samples 9
7.1 General 9
7.2 Samples containing less than 98 % (by mass) polyamide 9

8 Calculation of test portion 10

9 Selection of solvent 10

10 Procedure 11
10.1 Cleaning of the viscometer 11
10.2 Preparation of test solution 11
10.3 Measurement of flow times 13

11 Expression of results 14

12 Repeatability and reproducibility 14

13 Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents 15

14 Test report 15

Annex A (informative) Determination of the concentration of commercial sulfuric acid (95 % to 98 %) and adjustment to 96 % by titration 17

Annex B (informative) Determination of the concentration of sulfuric acid (95 % to 98 %) and adjustment to 96 % by flow time measurement in a small capillary viscometer 20

Annex C (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by titration 22

Annex D (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by density measurement 24

Annex E (informative) Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents 27

Bibliography 37