

ISO 4892-4:2013-08 (E)

Plastics - Methods of exposure to laboratory light sources - Part 4: Open-flame carbon-arc lamps

| Contents | | Page |
|--------------------|-------------------------------------------------------------|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Principle | 1 |
| 4 | Apparatus | 2 |
| 4.1 | Laboratory light source | 2 |
| 4.2 | Test chamber | 6 |
| 4.3 | Radiometer | 7 |
| 4.4 | Thermometer | 7 |
| 4.5 | Moisture | 7 |
| 4.6 | Specimen holders | 7 |
| 4.7 | Apparatus to assess changes in properties | 7 |
| 5 | Test specimens | 8 |
| 6 | Test conditions | 8 |
| 6.1 | Temperature | 8 |
| 6.2 | Relative humidity of air | 8 |
| 6.3 | Spray cycle | 8 |
| 6.4 | Cycles with dark periods | 8 |
| 7 | Procedure | 9 |
| 7.1 | Mounting the test specimens | 9 |
| 7.2 | Exposure | 9 |
| 7.3 | Measurement of radiant exposure | 9 |
| 7.4 | Determination of changes in properties after exposure | 9 |
| 8 | Exposure report | 9 |
| Bibliography | | 10 |