

# DIN EN 13553:2015-06 (E)

## Resilient floor coverings - Polyvinyl chloride floor coverings for use in special wet areas - Specification

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>4</b>
<b>4</b>	<b>Requirements .....</b>	<b>4</b>
<b>4.1</b>	<b>General requirements .....</b>	<b>4</b>
<b>4.2</b>	<b>Additional performance requirements .....</b>	<b>5</b>
<b>4.3</b>	<b>Installation .....</b>	<b>5</b>
<b>5</b>	<b>Marking .....</b>	<b>5</b>
<b>Annex A (normative)</b>	<b>Water tightness test .....</b>	<b>6</b>
<b>A.1</b>	<b>Scope .....</b>	<b>6</b>
<b>A.2</b>	<b>Apparatus .....</b>	<b>6</b>
<b>A.3</b>	<b>Test specimen .....</b>	<b>6</b>
<b>A.4</b>	<b>Conditioning .....</b>	<b>7</b>
<b>A.5</b>	<b>Testing .....</b>	<b>7</b>
<b>A.6</b>	<b>Test report .....</b>	<b>8</b>
<b>Annex B (informative)</b>	<b>Choice of floor covering category .....</b>	<b>9</b>
<b>Annex C (informative)</b>	<b>Installation .....</b>	<b>10</b>
<b>Annex D (informative)</b>	<b>Determination of elongation at break (optional property) .....</b>	<b>11</b>
<b>D.1</b>	<b>Apparatus, sampling and preparation of test pieces .....</b>	<b>11</b>
<b>D.2</b>	<b>Procedure .....</b>	<b>11</b>
<b>D.3</b>	<b>Calculation and expression of result .....</b>	<b>11</b>
<b>D.4</b>	<b>Requirement .....</b>	<b>11</b>
<b>D.5</b>	<b>Test report .....</b>	<b>11</b>