

DIN ISO 16486-3:2015-07 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 3: Fittings (ISO 16486-3:2012 + AMD 1:2014)

Contents		Page
National foreword		3
National Annex NA (informative) Bibliography		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms, definitions, symbols and abbreviated terms	7
4	Material	8
4.1	PA-U compound	8
4.2	Material for unplasticized polyamide parts	8
5	General characteristics	9
5.1	Appearance	9
5.2	Design	9
5.3	Colour	9
5.4	Electrical characteristics for electrofusion fittings	9
5.5	Appearance of factory-made joints	9
5.6	Fusion compatibility	9
6	Geometrical characteristics	10
6.1	Measurement of dimensions	10
6.2	Dimensions of electrofusion sockets	10
6.3	Dimensions of spigot end fittings	12
6.4	Dimensions of tapping tees	13
6.5	Dimensions of transition fittings to other materials	14
7	Mechanical characteristics	14
7.1	General	14
7.2	Conditioning	14
7.3	Requirements	14
8	Physical characteristics	15
8.1	Conditioning	15
8.2	Requirements	16
9	Chemical resistance of fittings in contact with chemicals	16
10	Performance requirements	16
11	Marking	16
11.1	General	16
11.2	Minimum required marking of fittings	16
11.3	Additional information required on fitting or label	17
11.4	Fusion system recognition	17

12	Packaging	17
	Annex A (informative) Examples of typical terminal connections for electrofusion fittings	18
	Annex B (normative) Short-term pressure test method	20
	Annex C (normative) Tensile test fitting/pipe assemblies	22
	Bibliography	23