ISO 16486-4:2016-06 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 4: Valves

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2

4 Material 3
4.1 PA-U compound 3
4.2 Material for non-unplasticized polyamide parts 3
4.2.1 General 3
4.2.2 Metal parts 4
4.2.3 Elastomers 4
4.2.4 Other materials 4

5 General characteristics 4
5.1 Appearance of the valve 4
5.2 Colour 4
5.3 Design 4
5.3.1 General 4
5.3.2 Valve body 4
5.3.3 Operating device 5
5.3.4 Seals 5
5.4 Fusion compatibility 5

6 Geometrical characteristics 5
6.1 General 5
6.2 Measurement of dimensions 5
6.3 Dimensions of spigot ends for valves 5
6.4 Dimensions of valves with electrofusion sockets 5
6.5 Dimensions of the operating device 6

7 Mechanical characteristics of assembled valves 6
7.1 General 6
7.2 Conditioning 6
7.3 Requirements 6

8 Physical characteristics 11
8.1 Conditioning 11
8.2 Requirement 11

9 Performance requirements 11

10 Marking 12
10.1 General 12
10.2 Minimum required marking of valves 12
10.3 Additional information required on valve or label 12
10.4 Fusion system recognition 12

11 Packaging 13

Annex A (normative) Determination of the leaktightness of seat and packing 14

Annex B (normative) Test method for leaktightness and ease of operation after tensile loading 15

Bibliography 17