

ISO 5659-2:2017-05 (E)

Plastics - Smoke generation - Part 2: Determination of optical density by a single-chamber test

Contents	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principles of the test	3
5 Suitability of a material or product for testing	3
5.1 Material or product geometry	3
5.2 Surface characteristics	3
5.3 Asymmetrical products	3
6 Specimen construction and preparation	4
6.1 Number of specimens	4
6.2 Size of specimens	4
6.3 Specimen preparation	4
6.4 Conditioning	5
6.5 Wrapping of specimens	5
7 Apparatus and ancillary equipment	5
7.1 General	5
7.2 Test chamber	6
7.2.1 Construction	6
7.2.2 Chamber pressure control facilities	6
7.2.3 Chamber wall temperature	9
7.3 Specimen support and heating arrangements	10
7.3.1 Radiator cone	10
7.3.2 Framework for support of the radiator cone, specimen holder and heat flux meter	10
7.3.3 Radiator shield	13
7.3.4 Heat flux meter	13
7.3.5 Specimen holder	14
7.3.6 Pilot burner	14
7.4 Gas supply	15
7.5 Photometric system	15
7.5.1 General	15
7.5.2 Light source	15
7.5.3 Photo detector	15
7.5.4 Additional equipment	17
7.6 Chamber leakage	17
7.7 Cleaning materials	18
7.8 Ancillary equipment	18
7.8.1 Balance	18
7.8.2 Timing device	18
7.8.3 Linear measuring devices	18
7.8.4 Auxiliary heater	18
7.8.5 Protective equipment	18
7.8.6 Recorder	18
7.8.7 Water-circulating device	18

8	Test environment	18
9	Setting-up and calibration procedures	19
9.1	General	19
9.2	Alignment of photometric system	19
9.2.1	General	19
9.2.2	Beam collimation	19
9.2.3	Beam focusing	19
9.3	Selection of compensating filter(s)	19
9.4	Linearity check	20
9.5	Calibration of range-extension filter	20
9.6	Chamber leakage rate test	21
9.7	Burner calibration	21
9.8	Radiator cone calibration	21
9.9	Cleaning	22
9.10	Frequency of checking and calibrating procedure	22
10	Test procedure	22
10.1	General	22
10.2	Preparation of test chamber	22
10.3	Tests with pilot flame	23
10.4	Preparation of the photometric system	23
10.5	Loading the specimen	23
10.6	Recording of light transmission	23
10.7	Observations	24
10.8	Termination of test	24
10.9	Testing in different modes	25
11	Expression of results	25
11.1	Specific optical density, D_s	25
11.2	Clear-beam correction factor, D_c	26
12	Precision	26
13	Test report	26
Annex A (normative) Calibration of heat flux meter		28
Annex B (informative) Variability in the specific optical density of smoke measured in the single-chamber test		29
Annex C (informative) Determination of mass optical density		31
Annex D (informative) Precision data from tests on intumescent materials		36
Annex E (informative) Guidance on optical density testing		38
Annex F (informative) Specific sample preparation		46
Bibliography		49