

ISO 2411:2017-09 (E)

Rubber- or plastics-coated fabrics - Determination of coating adhesion

| Contents | | Page |
|-----------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Atmosphere for conditioning and testing | 2 |
| 4.1 | For conditioning | 2 |
| 4.2 | For testing | 2 |
| 5 | Time-interval between manufacture and testing | 2 |
| 6 | Preparation of test specimens | 3 |
| 6.1 | General | 3 |
| 6.2 | Method of preparation 1 | 3 |
| 6.3 | Method of preparation 2 | 3 |
| 6.4 | Determination of wet coating adhesion | 4 |
| 6.4.1 | End-use | 4 |
| 6.4.2 | Preparation of test specimens | 4 |
| 6.4.3 | Conducting the test | 4 |
| 7 | Apparatus | 4 |
| 8 | Procedure | 5 |
| 9 | Calculation and expression of results | 5 |
| 9.1 | General | 5 |
| 9.2 | Determination of mid-point value | 5 |
| 9.3 | Calculation of mean result | 5 |
| 9.4 | Coating adhesion strength | 6 |
| 10 | Test report | 6 |
| Annex A (informative) | Comments on interpretation of the autographic traces | 11 |