

DIN EN ISO 11357-6:2018-07 (E)

Plastics - Differential scanning calorimetry (DSC) - Part 6: Determination of oxidation induction time (isothermal OIT) and oxidation induction temperature (dynamic OIT) (ISO 11357-6:2018)

Contents	Page
European foreword	3
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Principle	7
4.1 General	7
4.2 Oxidation induction time (isothermal OIT)	7
4.3 Oxidation induction temperature (dynamic OIT)	7
5 Apparatus and materials	8
5.1 General	8
5.2 DSC instrument	8
5.3 Crucibles	8
5.4 Flowmeter	8
5.5 Oxygen	8
5.6 Air	3
5.7 Nitrogen	8
5.8 Gas-selector switch and regulators	8
6 Test specimens	9
6.1 General	9
6.2 Specimens from compression-moulded plates	9
6.3 Specimens from injection-moulded plates or melt flow extrudates	9
6.4 Specimens from finished parts	9
7 Test conditions and specimen conditioning	10
8 Calibration	10
8.1 Oxidation induction time (isothermal OIT)	10
8.2 Oxidation induction temperature (dynamic OIT)	10
9 Procedure	10
9.1 Setting up the instrument	10
9.2 Loading the test specimen into the crucible	10
9.3 Insertion of crucibles	10
9.4 Nitrogen, air and oxygen flow	10
9.5 Sensitivity adjustment	11
9.6 Performance of measurement	11
9.6.1 Oxidation induction time (isothermal OIT)	11
9.6.2 Oxidation induction temperature (dynamic OIT)	12
9.7 Cleaning	12
10 Expression of results	13
11 Precision and bias	15
12 Test report	15
Bibliography	17