DIN 16873:2018-09 (E)

Pipes and fittings of unplasticized poly(vinyl chloride) (PVC-U) for cable ducting - Dimensions and technical delivery conditions

Contents

Page

Foreword ... 4

1 Scope ... 5

2 Normative references ... 5

3 Terms and definitions ... 6

4 Symbols and abbreviations ... 7
4.1 Symbols ... 7
4.2 Abbreviations ... 7

5 Dimensions, designation ... 8
5.1 General ... 8
5.2 Pipes ... 8
5.2.1 General ... 8
5.2.2 Pipe outside diameters and wall thicknesses ... 8
5.3 Fittings ... 10

6 Material ... 10
6.1 Pipes and fittings ... 10
6.2 Seals ... 10
6.3 Adhesives ... 10

7 Requirements ... 10
7.1 General ... 10
7.2 Appearance ... 10
7.3 Colour ... 11
7.4 Dimensions and tolerances ... 11
7.5 Strength properties ... 11
7.5.1 Long-term hydrostatic strength ... 11
7.5.2 Resistance to external blows ... 11
7.6 Heat reversion ... 12
7.7 Vicat softening temperature ... 12

8 Testing ... 12
8.1 Appearance ... 12
8.2 Colour ... 12
8.3 Dimensions ... 12
8.4 Strength properties ... 13
8.4.1 Long-term hydrostatic strength ... 13
8.4.2 Resistance to external blows ... 13
8.5 Heat reversion ... 13
8.6 Vicat softening temperature ... 13

9 Marking ... 13
9.1 General ... 13
9.2 Minimum marking of pipes ... 14

10 Laying instructions ... 14
10.1 Structural strength ... 14

10.2 Installation of pipes and fittings **14**

Annex A (normative) **Fittings for straight pipes** **15**
A.1 Dimensions **15**
A.2 Requirements **20**
A.3 Testing of injection-moulded fittings **21**
A.4 Additional marking **21**

Annex B (informative) **Terms which are not used in this standard, but are of relevance for the user** **22**

Bibliography **23**