

ISO 4586-2:2018 (E)

High-pressure decorative laminates (HPL, HPDL) — Sheets based on thermosetting resins (usually called laminates) — Part 2: Determination of properties

Contents

| | |
|-----|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Assessment of appearance |
| 4.1 | Principle |
| 4.2 | Apparatus |
| 4.3 | Test specimen |
| 4.4 | Procedure |
| 4.5 | Test report |
| 5 | Determination of thickness |
| 5.1 | Principle |
| 5.2 | Apparatus |
| 5.3 | Test specimen |
| 5.4 | Procedure |
| 5.5 | Test report |
| 6 | Determination of length and width |
| 6.1 | Principle |
| 6.2 | Apparatus |
| 6.3 | Test specimen |
| 6.4 | Procedure |
| 6.5 | Expression of results |
| 6.6 | Test report |
| 7 | Determination of edge straightness |
| 7.1 | Principle |
| 7.2 | Apparatus |
| 7.3 | Test specimen |
| 7.4 | Procedure |
| 7.5 | Expression of results |
| 7.6 | Test report |
| 8 | Determination of edge squareness (Method A) |
| 8.1 | Principle |
| 8.2 | Apparatus |
| 8.3 | Test specimen |
| 8.4 | Procedure |
| 8.5 | Expression of results |
| 8.6 | Test report |
| 9 | Determination of edge squareness (Method B) |
| 9.1 | Principle |
| 9.2 | Apparatus |
| 9.3 | Test specimen |

- 9.4 Procedure
- 9.5 Expression of results
- 9.6 Test report
- 10 Determination of flatness
 - 10.1 Principle
 - 10.2 Apparatus
 - 10.3 Test specimens
 - 10.4 Procedure
 - 10.5 Expression of results
 - 10.6 Test report
- 11 Resistance to surface wear
 - 11.1 Principle
 - 11.2 Materials
 - 11.3 Apparatus
 - 11.4 Test specimens
 - 11.5 Preparation of specimens and abrasive paper
 - 11.6 Procedure
 - 11.6.1 Preparation of abrasive wheels
 - 11.6.2 Calibration of abrasive paper
 - 11.6.3 Abrasion of specimen
 - 11.7 Expression of results
 - 11.8 Test report
- 12 Resistance to abrasion (Flooring grade laminates)
 - 12.1 Principle
 - 12.2 Materials
 - 12.3 Apparatus
 - 12.4 Test specimens
 - 12.5 Preparation of specimens and abrasive paper
 - 12.6 Procedure
 - 12.6.1 Preparation of abrasive wheels
 - 12.6.2 Calibration of abrasive paper
 - 12.6.3 Abrasion of specimen
 - 12.7 Expression of results
 - 12.8 Test report
- 13 Resistance to immersion in boiling water
 - 13.1 Principle
 - 13.2 Apparatus
 - 13.3 Test specimens
 - 13.4 Procedure
 - 13.5 Expression of results
 - 13.6 Test report
- 14 Substrate protection against water vapour
 - 14.1 Principle
 - 14.2 Apparatus
 - 14.3 Test specimens
 - 14.4 Procedure
 - 14.5 Expression of results
 - 14.6 Test report
- 15 Resistance to water vapour
 - 15.1 Principle
 - 15.2 Apparatus
 - 15.3 Test specimen
 - 15.4 Procedure
 - 15.5 Expression of results
 - 15.6 Test report
- 16 Resistance to wet conditions (Exterior grade laminates)
 - 16.1 Principle

- 16.2 Apparatus
- 16.3 Test specimens
- 16.4 Procedure
- 16.5 Expression of results
- 16.6 Test report
- 17 Resistance to dry heat (Method A)
 - 17.1 Principle
 - 17.2 Apparatus and materials
 - 17.3 Test specimen
 - 17.4 Test procedure
 - 17.5 Examination of the test specimen
 - 17.6 Expression of results
 - 17.7 Test report
- 18 Resistance to dry heat (Method B)
 - 18.1 Principle
 - 18.2 Materials
 - 18.3 Apparatus
 - 18.4 Test specimen
 - 18.5 Procedure
 - 18.6 Expression of results
 - 18.7 Test report
- 19 Dimensional stability at elevated temperature (Method A)
 - 19.1 Principle
 - 19.2 Apparatus
 - 19.3 Test specimens
 - 19.4 Procedure
 - 19.5 Expression of results
 - 19.6 Test report
- 20 Dimensional stability at elevated temperature (Method B)
 - 20.1 Principle
 - 20.2 Apparatus
 - 20.3 Test specimens
 - 20.4 Procedure
 - 20.4.1 General
 - 20.5 Expression of results
 - 20.6 Test report
- 21 Dimensional stability at ambient temperature (Method A)
 - 21.1 Principle
 - 21.2 Apparatus
 - 21.3 Test specimens
 - 21.4 Procedure
 - 21.5 Expression of results
 - 21.6 Test report
- 22 Dimensional stability at ambient temperature (Method B)
 - 22.1 Principle
 - 22.2 Apparatus
 - 22.3 Test specimens
 - 22.4 Procedure
 - 22.5 Expression of results
 - 22.6 Test report
- 23 Resistance to climatic shock (exterior grade laminates)
 - 23.1 Principle
 - 23.2 Apparatus
 - 23.3 Test specimens
 - 23.4 Procedure
 - 23.5 Expression of results
 - 23.6 Test report

- 24 Resistance to impact by small diameter ball**
 - 24.1 Principle
 - 24.2 Materials
 - 24.3 Apparatus
 - 24.4 Test specimens
 - 24.5 Calibration of the impact tester
 - 24.6 Procedure
 - 24.7 Expression of results
 - 24.8 Test report
- 25 Resistance to impact by large diameter ball**
 - 25.1 Principle
 - 25.2 Materials
 - 25.3 Apparatus
 - 25.4 Test specimens
 - 25.5 Procedure
 - 25.6 Expression of results
 - 25.7 Test report
- 26 Resistance to impact by large diameter ball (Flooring grade laminates)**
 - 26.1 Principle
 - 26.2 Materials
 - 26.3 Apparatus
 - 26.4 Test specimens
 - 26.5 Procedure
 - 26.6 Expression of results
 - 26.7 Test report
- 27 Resistance to cracking under stress (Laminates \leq 2 mm thick)**
 - 27.1 Principle
 - 27.2 Apparatus
 - 27.3 Test specimens
 - 27.4 Procedure
 - 27.5 Expression of results
 - 27.6 Test report
- 28 Resistance to crazing (Compact laminates)**
 - 28.1 Principle
 - 28.2 Apparatus
 - 28.3 Test specimens
 - 28.4 Procedure
 - 28.5 Expression of results
 - 28.6 Test report
- 29 Resistance to scratching**
 - 29.1 Principle
 - 29.2 Materials
 - 29.3 Apparatus
 - 29.4 Calibration of apparatus
 - 29.5 Test specimen
 - 29.6 Procedure
 - 29.7 Expression of results
 - 29.8 Test report
- 30 Resistance to staining (Method A)**
 - 30.1 Principle
 - 30.2 Staining agents
 - 30.3 Materials
 - 30.4 Apparatus
 - 30.5 Test specimens
 - 30.6 Procedure
 - 30.7 Expression of results
 - 30.8 Test report

- 31 **Resistance to staining (Method B)**
 - 31.1 **Principle**
 - 31.2 **Materials**
 - 31.3 **Apparatus**
 - 31.4 **Test specimens**
 - 31.5 **Procedure**
 - 31.6 **Expression of results**
 - 31.7 **Test report**

- 32 **Lightfastness (xenon arc) (Method A)**
 - 32.1 **Principle**
 - 32.2 **Apparatus**
 - 32.3 **Test specimen**
 - 32.4 **Procedure**
 - 32.5 **Assessment and expression of results**
 - 32.6 **Test report**

- 33 **Lightfastness (xenon arc) (Method B)**
 - 33.1 **Principle**
 - 33.2 **Apparatus**
 - 33.3 **Test specimen**
 - 33.4 **Procedure**
 - 33.5 **Expression of results**
 - 33.6 **Test report**

- 34 **Resistance to UV light (Exterior grade laminates)**
 - 34.1 **Principle**
 - 34.2 **Apparatus**
 - 34.3 **Test specimens**
 - 34.4 **Procedure**
 - 34.5 **Evaluation and expression of results**
 - 34.5.1 **Contrast**
 - 34.5.2 **Appearance**
 - 34.6 **Test report**

- 35 **Resistance to artificial weathering (Exterior grade laminates)**
 - 35.1 **Principle**
 - 35.2 **Apparatus**
 - 35.3 **Test specimens**
 - 35.4 **Procedure**
 - 35.5 **Examination and expression of results**
 - 35.5.1 **General**
 - 35.5.2 **Contrast**
 - 35.5.3 **Appearance**
 - 35.6 **Test report**

- 36 **Resistance to radiant heat**
 - 36.1 **Principle**
 - 36.2 **Apparatus**
 - 36.3 **Test specimen**
 - 36.4 **Procedure**
 - 36.5 **Test report**

- 37 **Formability (Method A)**
 - 37.1 **Principle**
 - 37.2 **Apparatus**
 - 37.3 **Test specimens**
 - 37.4 **Procedure**
 - 37.4.1 **General**
 - 37.4.2 **Calibration of test apparatus**
 - 37.4.3 **Test procedure**
 - 37.5 **Test report**

- 38 Formability (Method B)**
 - 38.1 Principle
 - 38.2 Apparatus
 - 38.3 Test specimens
 - 38.4 Procedure
 - 38.4.1 Calibration of test apparatus
 - 38.4.2 Test procedure
 - 38.5 Test report
- 39 Resistance to blistering (Method A)**
 - 39.1 Principle
 - 39.2 Apparatus
 - 39.3 Test specimens
 - 39.4 Procedure
 - 39.4.1 Calibration of test apparatus
 - 39.4.2 Test procedure
 - 39.5 Test report
- 40 Resistance to blistering (Method B)**
 - 40.1 Principle
 - 40.2 Apparatus
 - 40.3 Test specimens
 - 40.4 Procedure
 - 40.5 Test procedure
 - 40.6 Test report
- 41 Resistance to wet heat (100 °C)**
 - 41.1 Principle
 - 41.2 Apparatus
 - 41.3 Test specimen
 - 41.4 Procedure
 - 41.5 Expression of results
 - 41.6 Test report
- 42 Determination of microscratch resistance**
 - 42.1 Principle
 - 42.2 Apparatus
 - 42.3 Materials
 - 42.4 Calibration
 - 42.4.1 Assembly and maintenance of the Martindale tester
 - 42.4.2 Method for checking the Lissajous figure
 - 42.5 Test specimens
 - 42.5.1 Preparation
 - 42.5.2 Test surface
 - 42.6 Procedure
 - 42.6.1 General
 - 42.6.2 Method
 - 42.6.2.1 Procedure A
 - 42.6.2.2 Procedure B
 - 42.7 Classification of the image after testing to procedure B
 - 42.8 Test report