

# ISO 17281:2018 (E)

## Plastics — Determination of fracture toughness (GIC and KIC) at moderately high loading rates (1 m/s)

---

### Contents

|         |  |
|---------|--|
|         | Foreword   |
|         | Introduction   |
| 1       | Scope  |
| 2       | Normative references   |
| 3       | Terms and definitions  |
| 4       | Test specimens   |
| 4.1     | Specimen geometry and preparation                                      |
| 4.2     | Crack length and number of test replicates                             |
| 4.2.1   | Determination of KIC   |
| 4.2.2   | Determination of GIC   |
| 4.3     | Measurement of test specimen dimensions                                |
| 5       | Test conditions  |
| 5.1     | Loading mode   |
| 5.2     | Test speed   |
| 5.3     | Test atmosphere and temperature  |
| 6       | Test equipment   |
| 6.1     | Loading machine  |
| 6.2     | Loading rigs   |
| 6.3     | Instrumentation  |
| 7       | Control of dynamic effects   |
| 7.1     | Electronic filtering   |
| 7.2     | Mechanical damping   |
| 7.3     | Damping level  |
| 7.4     | Check on speed   |
| 8       | Data handling  |
| 8.1     | Analysis of the test records and identification of fracture initiation |
| 8.2     | Energy correction  |
| 8.2.1   | General  |
| 8.2.2   | Test piece indentation, machine compliance and damper compression      |
| 8.2.3   | Kinetic energy and inertial loads                                      |
| 9       | Expression of results  |
| 9.1     | Determination of KIC   |
| 9.2     | Determination of $\sigma_y$  |
| 9.3     | Determination of GIC   |
| 10      | Precision  |
| 11      | Test report  |
| Annex A | (informative) Estimation of curve fit parameters                       |
| Annex B | (informative) Recommended test report forms                            |

**Annex C (informative) Testing of plastics containing short fibres**

- C.1 General**
- C.2 Identification of fracture initiation**
  - C.2.1 Determination of KIC**
  - C.2.2 Determination of GIC**

**Page count: 28**