

ISO 20457:2018 (E)

Plastics moulded parts — Tolerances and acceptance conditions

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	General
4.2	Symbols
4.3	Abbreviated terms
5	Tolerancing of plastic moulded parts
5.1	General
5.2	Intention
5.3	General tolerances
5.4	Direct tolerancing (individual tolerancing)
5.5	Tolerancing of draft angles
5.6	Dimensioning, tolerancing and measuring of radii
5.7	Specification of freeform surfaces
6	Moulding compound properties
6.1	General
6.2	Moulding shrinkage and shrinkage anisotropies
6.3	Moulded material stiffness or hardness
7	Dimensional and geometrical tolerancing
7.1	Dimensional tolerancing
7.1.1	Tolerance grades for features of sizes
7.1.2	Determination of the tolerance grades
7.1.2.1	General
7.1.2.2	Evaluation of the production process and moulding compound properties (P1 to P4)
7.1.2.3	Evaluation of the production expense (P5)
7.2	Geometrical tolerancing
7.3	Parting line/Tool offset
7.4	Tolerancing of angular dimensions
8	Acceptance conditions for moulded part production (ABF)
Annex A	(informative) Dimensional reference levels for application and production of the moulded parts
A.1	Sizes and dimensional relations
A.2	Application conditions
A.3	Moulding-induced dimensional shift, ΔLV
Annex B	(informative) Causes and influential factors on the moulding shrinkage of non-porous plastics
Annex C	(informative) Evaluation of the production expense
Annex D	(informative) Validation of machine or process capability

- Annex E (informative) Main causes for dimension, form and location deviations in moulded part production**
- Annex F (informative) Example for determining the DP dimension for application of Table 9**
- Annex G (informative) Feasible acceptance parameters**

Page count: 28