ISO 20457:2018 (E)

Plastics moulded parts — Tolerances and acceptance conditions

Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Symbols and abbreviated terms
 - 4.1 General
 - 4.2 Symbols
 - 4.3 Abbreviated terms
- 5 Tolerancing of plastic moulded parts
 - 5.1 General
 - 5.2 Intention
 - 5.3 General tolerances
 - 5.4 Direct tolerancing (individual tolerancing)
 - 5.5 Tolerancing of draft angles
 - 5.6 Dimensioning, tolerancing and measuring of radii
 - 5.7 Specification of freeform surfaces
- 6 Moulding compound properties
 - 6.1 General
 - 6.2 Moulding shrinkage and shrinkage anisotropies
 - 6.3 Moulded material stiffness or hardness
- 7 Dimensional and geometrical tolerancing
 - 7.1 Dimensional tolerancing
 - 7.1.1 Tolerance grades for features of sizes
 - 7.1.2 Determination of the tolerance grades
 - 7.1.2.1 General
 - 7.1.2.2 Evaluation of the production process and moulding compound properties (P1 to P4)
 - 7.1.2.3 Evaluation of the production expense (P5)
 - 7.2 Geometrical tolerancing
 - 7.3 Parting line/Tool offset
 - 7.4 Tolerancing of angular dimensions
- 8 Acceptance conditions for moulded part production (ABF)
- Annex A (informative) Dimensional reference levels for application and production of the moulded parts
 - A.1 Sizes and dimensional relations
 - A.2 Application conditions
 - A.3 Moulding-induced dimensional shift, \triangle LV
- Annex B (informative) Causes and influential factors on the moulding shrinkage of non-porous plastics
- Annex C (informative) Evaluation of the production expense
- Annex D (informative) Validation of machine or process capability

- Annex E (informative) Main causes for dimension, form and location deviations in moulded part production
- Annex F (informative) Example for determining the DP dimension for application of Table 9
- Annex G (informative) Feasible acceptance parameters

Page count: 28