ISO 19935-1:2018 (E)

Plastics — Temperature modulated DSC — Part 1: General principles

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Calculation of heat flow rate and heat capacity

- 4.1 Temperature modulation, T(t)
- 4.2 Heating rate
- 4.3 Heat flow rate Φ(t) and heat capacity
- 4.3.1 General
- 4.3.2 Heat capacity with no processes
- 4.3.3 Heat capacity with additional processes
- 4.3.4 Time dependent heat capacity

5 Principles

- 5.1 General
- 5.2 Mode of temperature modulation
- 5.2.1 Variable heating rate of periodic modulation
- 5.2.2 Variable temperature modulated mode
- 5.3 Heat capacity determined with the temperature modulation — Complex heat capacity
- 5.4 Reversing and non-reversing heat capacity
- 5.5 Advantage of the temperature modulation applied to DSC

6 Apparatus and materials

- 6.1 General
- 6.2 Temperature control of modulated differential scanning calorimeter

7 Calibration

- 7.1 General
- 7.2 Calibration of modulation amplitude
- 7.3 Calibration of phase

8 Procedure

- 8.1 General
- 8.2 Experimental conditions
- 8.3 Interpretation of results

9 Test report

Annex A (informative) Generalized theory of temperature modulated DSC[7]

Page count: 16