

# DIN EN ISO 307:2019-11 (E)

## Plastics - Polyamides - Determination of viscosity number (ISO 307:2019)

---

<b>Contents</b>	<b>Page</b>
<b>European foreword</b> .....	<b>3</b>
<b>Foreword</b> .....	<b>4</b>
<b>Introduction</b> .....	<b>5</b>
<b>1 Scope</b> .....	<b>6</b>
<b>2 Normative references</b> .....	<b>6</b>
<b>3 Terms and definitions</b> .....	<b>6</b>
<b>4 Principle</b> .....	<b>8</b>
<b>5 Reagents and materials</b> .....	<b>8</b>
5.1 Solvents and reagents .....	8
5.2 Cleaning liquids .....	9
<b>6 Apparatus</b> .....	<b>9</b>
<b>7 Preparation of test samples</b> .....	<b>10</b>
7.1 General .....	10
7.2 Samples containing less than 98 % (by mass) polyamide .....	11
<b>8 Calculation of test portion</b> .....	<b>11</b>
<b>9 Selection of solvent</b> .....	<b>11</b>
<b>10 Procedure</b> .....	<b>12</b>
10.1 Cleaning of the viscometer .....	12
10.2 Preparation of test solution .....	12
10.2.1 General .....	12
10.2.2 Volumetric method .....	13
10.2.3 Volumetric method, in exact relation to the polymer content .....	13
10.2.4 Gravimetric method, in exact relation to the polymer content .....	13
10.3 Measurement of flow times .....	14
<b>11 Expression of results</b> .....	<b>15</b>
<b>12 Repeatability and reproducibility</b> .....	<b>16</b>
<b>13 Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents</b> .....	<b>16</b>
<b>14 Test report</b> .....	<b>16</b>
<b>Annex A (informative) Determination of the concentration of commercial sulfuric acid(95 % to 98 %) and adjustment to 96 % by titration</b> .....	<b>17</b>
<b>Annex B (informative) Determination of the concentration of sulfuric acid (95 % to 98 %) and adjustment to 96 % by flow time measurement in a small capillary viscometer</b> .....	<b>20</b>
<b>Annex C (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by titration</b> .....	<b>22</b>
<b>Annex D (informative) Determination of the concentration of commercial formic acid and adjustment to 90 % by density measurement</b> .....	<b>24</b>
<b>Annex E (informative) Relationship between the viscosity number determined in 96 % (by mass) sulfuric acid solution and the viscosity determined in various solvents</b> .....	<b>27</b>
<b>Bibliography</b> .....	<b>39</b>