

ISO/TR 20118:2019-04 (E)

Plastics - Guidance on fire characteristics and fire performance of PVC materials used in building applications

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	PVC building materials and products	3
4.1	Definition and description	3
4.1.1	General	3
4.1.2	PVC-U based products	4
4.1.3	PVC-P based products	4
4.1.4	PVC-C based products	5
4.1.5	Flame retardants	5
4.2	Product standards	6
5	Fire safety strategy	8
5.1	Fire safety objectives	8
5.1.1	General	8
5.1.2	Safety of life	9
5.1.3	Conservation of property	9
5.1.4	Continuity of business or service operations	10
5.1.5	Protection of the environment	10
5.1.6	Preservation of heritage	11
5.2	Fire scenarios	11
6	Fire test methods -- Description and relevance	13
6.1	General	13
6.1.1	Reaction to fire tests applicable to plastics construction products	13
6.1.2	Intermediate scale plastics reaction to fire tests	14
6.1.3	Fire stage and fire tests	14
6.1.4	Assessment of the fire threat to people	14
6.2	Relevance of results and studies comparisons	15
7	Material fire characteristics relevant for PVC construction products	16
7.1	Combustibility	16
7.2	Ignitability	18
7.2.1	Ignition temperature	18
7.2.2	Ignitability measured by the cone calorimeter test	19
7.3	Oxygen index	20
7.4	Heat release and heat release rate	21
7.4.1	General	21
7.4.2	Heat release data	22
7.5	Flame spread	24
7.5.1	General	24
7.5.2	Flame spread by flame propagation	26
7.5.3	Flame spread by flaming droplets	26
7.6	Smoke generation	27

7.6.1	Smoke obscuration	27
7.6.2	Smoke toxicity	28
7.6.3	Smoke corrosivity	31
7.6.4	HCl decay	32
7.7	Char formation and intumescence	33
Annex A (informative) Example of reaction to fire performance -- PVC-U pipe		34
Annex B (informative) Example case history -- Plastimet accident		35
Bibliography		36