ISO/TR 20118:2019-04 (E)

Plastics - Guidance on fire characteristics and fire performance of PVC materials used in building applications

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 PVC building materials and products 3
4.1 Definition and description 3
4.1.1 General 3
4.1.2 PVC-U based products 4
4.1.3 PVC-P based products 4
4.1.4 PVC-C based products 5
4.1.5 Flame retardants 5
4.2 Product standards 6

5 Fire safety strategy 8
5.1 Fire safety objectives 8
5.1.1 General 8
5.1.2 Safety of life 9
5.1.3 Conservation of property 9
5.1.4 Continuity of business or service operations 10
5.1.5 Protection of the environment 10
5.1.6 Preservation of heritage 11
5.2 Fire scenarios 11

6 Fire test methods -- Description and relevance 13
6.1 General 13
6.1.1 Reaction to fire tests applicable to plastics construction products 13
6.1.2 Intermediate scale plastics reaction to fire tests 14
6.1.3 Fire stage and fire tests 14
6.1.4 Assessment of the fire threat to people 14
6.2 Relevance of results and studies comparisons 15

7 Material fire characteristics relevant for PVC construction products 16
7.1 Combustibility 16
7.2 Ignitability 18
7.2.1 Ignition temperature 18
7.2.2 Ignitability measured by the cone calorimeter test 19
7.3 Oxygen index 20
7.4 Heat release and heat release rate 21
7.4.1 General 21
7.4.2 Heat release data 22
7.5 Flame spread 24
7.5.1 General 24
7.5.2 Flame spread by flame propagation 26
7.5.3 Flame spread by flaming droplets 26
7.6 Smoke generation 27

7.6.1 Smoke obscuration 27
7.6.2 Smoke toxicity 28
7.6.3 Smoke corrosivity 31
7.6.4 HCl decay 32
7.7 Char formation and intumescence 33

Annex A (informative) Example of reaction to fire performance -- PVC-U pipe 34

Annex B (informative) Example case history -- Plastimet accident 35

Bibliography 36