ISO 6721-2:2019 (E)

Plastics — Determination of dynamic mechanical properties — Part 2: Torsion-pendulum method

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Principle

5 Test apparatus

- 5.1 Pendulum
- 5.2 Inertial element
- 5.2.1 General
- 5.2.2 Method A (see Figure 1)
- 5.2.3 Method B (see Figure 2)
- 5.3 Clamps
- 5.4 Oscillation-inducing device
- 5.5 Oscillation-frequency and oscillation-amplitude recording equipment
- 5.6 Temperature-controlled chamber
- 5.7 Gas supply
- 5.8 Temperature-measurement device
- 5.9 Devices for measuring test-specimen dimensions

6 Test specimens

- 6.1 General
- 6.2 Shape and dimensions
- 6.3 Preparation

7 Number of specimens

8 Conditioning

9 Procedure

- 9.1 Test atmosphere
- 9.2 Measurement of specimen cross-section
- 9.3 Mounting the test specimens
- 9.4 Varying the temperature
- 9.5 Performing the test

10 Expression of results

- 10.1 Symbols and correction factors
- 10.2 Calculation of logarithmic decrement, Λ
- 10.3 Calculation of torsional storage modulus, G to ′
- 10.4 Calculation of torsional loss modulus, G to ″

11 Precision

12 Test report

Annex A (normative) Influence of longitudinal force, W

Annex B (informative) Damping correction factor, Fd

Annex C (informative) Dimensional correction factor, Fc