ISO 19935-2:2020 (E)

Plastics — Temperature modulated DSC — Part 2: Measurement of specific heat capacity cp

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and abbreviated terms

- 4.1 Temperature modulation, T(t)
- 4.2 Scanning rate
- 4.3 Heat flow rate, Φ(t)

5 Principles of determination of specific heat capacity with temperature modulated DSC

- 5.1 General
- 5.2 Specific heat capacity with no processes
- 5.3 Reversing and non-reversing specific heat capacity
- 5.4 Step scan method
- 5.5 Multiple frequencies

6 Apparatus and materials

- 6.1 General
- 6.2 Temperature control of the modulated differential scanning calorimeter

7 Calibration

- 7.1 General
- 7.2 Calibration of modulation amplitude
- 7.3 Calibration of phase

8 Procedure

- 8.1 General
- 8.2 Calculation of the specific heat capacity
- 8.3 Examples of the results
- 8.3.1 Modulated heat flow rate and scanning rate of modulation
- 8.3.2 Determination of specific heat capacity

9 Precision and bias

10 Test report

Annex A (informative) Example of the cp values of polystyrene (PS)

Annex B (informative) Example of the calibration constant K(ω) determined with the literature values of α-Al2O3[3]

Annex C (informative) Example of a reversing heat flow rate curve based on a modulated heat flow rate curve and a comparison with the specific heat capacity

Annex D (informative) Example of determination of specific heat capacity based on a multifrequency modulated heat flow rate curve

Page count: 14