

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Temperature modulation, $T(t)$
4.2	Scanning rate
4.3	Heat flow rate, $\Phi(t)$
5	Principles of determination of specific heat capacity with temperature modulated DSC
5.1	General
5.2	Specific heat capacity with no processes
5.3	Reversing and non-reversing specific heat capacity
5.4	Step scan method
5.5	Multiple frequencies
6	Apparatus and materials
6.1	General
6.2	Temperature control of the modulated differential scanning calorimeter
7	Calibration
7.1	General
7.2	Calibration of modulation amplitude
7.3	Calibration of phase
8	Procedure
8.1	General
8.2	Calculation of the specific heat capacity
8.3	Examples of the results
8.3.1	Modulated heat flow rate and scanning rate of modulation
8.3.2	Determination of specific heat capacity
9	Precision and bias
10	Test report
Annex A	(informative) Example of the c_p values of polystyrene (PS)
Annex B	(informative) Example of the calibration constant $K(\omega)$ determined with the literature values of $\alpha\text{-Al}_2\text{O}_3$ [3]
Annex C	(informative) Example of a reversing heat flow rate curve based on a modulated heat flow rate curve and a comparison with the specific heat capacity
Annex D	(informative) Example of determination of specific heat capacity based on a multifrequency modulated heat flow rate curve