

DIN EN 1555-4:2021-12 (E)

Plastics piping systems for the supply of gaseous fuels - Polyethylene (PE) - Part 4: Valves

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| Introduction | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 9 |
| 3.1 | General | 9 |
| 3.2 | Terms relating to design | 9 |
| 4 | Symbols and abbreviations | 10 |
| 5 | Material | 10 |
| 5.1 | Compound for valve body | 10 |
| 5.2 | Material for non-polyethylene parts | 10 |
| 5.2.1 | General | 10 |
| 5.2.2 | Metal parts | 11 |
| 5.2.3 | Sealing materials | 11 |
| 5.2.4 | Greases and lubricants | 11 |
| 5.2.5 | Assembly | 11 |
| 6 | General characteristics | 11 |
| 6.1 | Appearance of the valve | 11 |
| 6.2 | Colour | 11 |
| 6.3 | Design | 11 |
| 6.3.1 | General | 11 |
| 6.3.2 | Valve body | 11 |
| 6.3.3 | Valve ends | 11 |
| 6.3.4 | Operating device | 12 |
| 6.3.5 | Seals | 12 |
| 7 | Geometrical characteristics | 12 |
| 7.1 | General | 12 |
| 7.2 | Measurement of dimensions | 12 |
| 7.3 | Dimensions of spigot ends for valves | 12 |
| 7.4 | Dimensions of valves with electrofusion sockets | 12 |
| 7.5 | Dimensions of the operating device | 12 |
| 8 | Mechanical characteristics of assembled valves | 13 |
| 8.1 | General | 13 |
| 8.2 | Requirements | 13 |
| 8.2.1 | General | 13 |
| 8.2.2 | Air flow rate | 19 |
| 9 | Physical characteristics | 19 |
| 9.1 | Conditioning | 19 |
| 9.2 | Requirements | 19 |
| 10 | Performance requirements | 20 |

| | | |
|--|---------------------------------------|-----------|
| 11 | Technical file | 20 |
| 12 | Marking | 21 |
| 12.1 | General | 21 |
| 12.2 | Minimum required marking | 21 |
| 12.3 | Additional marking | 22 |
| 13 | Delivery conditions | 22 |
| Annex A (normative) Determination of the leaktightness of seat(s) and packing | | 23 |
| Annex B (normative) Test method for leaktightness and ease of operation after tensile loading | | 25 |
| | Bibliography | 27 |