

# ISO 11443:2021-02 (E)

## Plastics - Determination of the fluidity of plastics using capillary and slit-die rheometers

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	General principles .....	4
5	Apparatus .....	4
5.1	Test device .....	4
5.1.1	General .....	4
5.1.2	Rheometer barrel .....	5
5.1.3	Capillary dies (method A) .....	5
5.1.4	Slit dies (method B) .....	9
5.1.5	Piston .....	9
5.2	Temperature control .....	9
5.3	Measurement of temperature and calibration .....	10
5.3.1	Test temperature .....	10
5.3.2	Measurement of test temperature .....	10
5.3.3	Temperature calibration .....	10
5.4	Measurement of pressure and calibration .....	10
5.4.1	Test pressure .....	10
5.4.2	Pressure drop along the length of the slit die .....	11
5.4.3	Calibration .....	11
5.5	Measurement of the volume flow rate of the sample .....	11
6	Sampling .....	11
7	Procedure .....	11
7.1	Cleaning the test device .....	11
7.2	Selection of test temperatures .....	12
7.3	Preparation of samples .....	13
7.4	Preheating .....	13
7.5	Determination of the maximum permissible test duration .....	13
7.6	Determination of test pressure at constant volume flow rate: Method 2 .....	14
7.7	Determination of volume flow rate at constant test pressure: Method 1 .....	14
7.8	Waiting periods during measurement .....	14
7.9	Measurement of extrudate swelling .....	14
7.9.1	General .....	14
7.9.2	Measurement at room temperature .....	15
7.9.3	Measurement at the test temperature .....	15
8	Expression of results .....	15
8.1	Volume flow rate .....	15
8.2	Apparent shear rate .....	16
8.2.1	General .....	16
8.2.2	Method A: Capillary dies .....	16
8.2.3	Method B: Slit dies .....	16
8.3	Apparent shear stress .....	17

8.3.1	General .....	17
8.3.2	Method A: Capillary dies .....	17
8.3.3	Method B: Slit dies .....	17
8.4	True shear stress .....	17
8.4.1	General .....	17
8.4.2	Bagley correction for capillary dies (method A) .....	18
8.4.3	Bagley correction for slit dies (method B) .....	21
8.4.4	Direct determination using slit dies (method B) .....	22
8.5	True shear rate .....	22
8.5.1	General .....	22
8.5.2	Method A: Capillary dies .....	23
8.5.3	Method B: Slit dies .....	23
8.6	Viscosity .....	23
8.7	Determination of extrudate swelling .....	23
8.7.1	Measurement at room temperature .....	23
8.7.2	Measurement at the test temperature .....	24
9	Precision .....	24
10	Test report .....	25
10.1	General .....	25
10.2	Test conditions .....	25
10.3	Flow characteristics .....	26
10.3.1	General .....	26
10.3.2	Graphical representation .....	26
10.3.3	Individual values .....	27
10.4	Visual examination .....	27
Annex A (informative)	Method of correcting for the influence of H/B on the apparent shear rate.28	
Annex B (informative)	Measurement errors .....	30
Annex C (informative)	Uncertainties in the determination of shear viscosity by capillary extrusion rheometry testing .....	31
Bibliography	.....	36