ISO 4589-4:2021 (E)

Plastics — Determination of burning behaviour by oxygen index — Part 4: High gas velocity test

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Principles for determination of HOI

5 Apparatus

6 Calibration of equipment

7 Preparation of test specimens

- 7.1 Test specimen form
- 7.2 Sampling
- 7.3 Test specimen dimensions and preparation
- 7.4 Marking of test specimen
- 7.5 Conditioning

8 Procedure for determination of HOI

- 8.1 Setting up the apparatus
- 8.2 Setting volume fraction of oxygen and gas flow velocity
- 8.3 Procedure for ignition of the test specimen
- 8.4 Assessing the burning behaviour of test specimen
- 8.5 Selecting successive volume fraction of oxygen
- 8.6 Determining the preliminary volume fraction of oxygen
- 8.7 Volume fraction of oxygen changes

9 Calculation and expression of results

- 9.1 Calculation of the HOI
- 9.2 Determination of k
- 9.3 Standard deviation of oxygen volume fraction measurements

10 Precision of test results

11 Test report

Annex A (normative) Calibration of equipment

- A.1 Leak tests
- A.2 Gas flow rates
- A.3 Gas velocity
- A.4 Oxygen analyser
- A.5 Mass flow controller
- A.6 Temperature measurement device

Annex B (informative) Example of test results sheet for HOI

- B.1 Test results sheet for HOI
- B.2 Determination of oxygen volume fraction for one pair of “X” and “O” responses at ≤1 % O2 volume fraction interval

B.3 Determination of HOI
B.4 Verification of step size d % oxygen volume fraction
B.5 Ancillary information

Annex C (informative) Interlaboratory test data on HOI measurement

Annex D (informative) Blow-off behaviour at high gas velocity — How to predict the flammability of materials

D.1 Background
D.2 Analytical model for flammability limiting curve
D.3 Relationship between the blow-off behaviour and flammability in microgravity

Page count: 29