

DIN EN ISO 16486-4:2022-06 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 4: Valves (ISO 16486-4:2022)

| Contents | | Page |
|--|---|-------------|
| European foreword | | 4 |
| Annex (informative) A-deviation | | 5 |
| Foreword | | 6 |
| Introduction | | 8 |
| 1 | Scope | 9 |
| 2 | Normative references | 9 |
| 3 | Terms and definitions | 10 |
| 3.1 | General..... | 11 |
| 3.2 | Terms relating to design..... | 11 |
| 4 | Symbols and abbreviated terms | 11 |
| 5 | Material | 12 |
| 5.1 | Compound for valve body..... | 12 |
| 5.1.1 | Compound..... | 12 |
| 5.1.2 | Fusion compatibility..... | 12 |
| 5.2 | Material for non-polyamide parts..... | 12 |
| 5.2.1 | General..... | 12 |
| 5.2.2 | Metal parts..... | 12 |
| 5.2.3 | Elastomers..... | 13 |
| 5.2.4 | Greases and lubricants..... | 13 |
| 5.2.5 | Assembly..... | 13 |
| 6 | General characteristics | 13 |
| 6.1 | Appearance of the valve..... | 13 |
| 6.2 | Colour..... | 13 |
| 6.3 | Design..... | 13 |
| 6.3.1 | General..... | 13 |
| 6.3.2 | Valve body..... | 13 |
| 6.3.3 | Valve terminal ends..... | 13 |
| 6.3.4 | Operating device..... | 13 |
| 6.3.5 | Seals..... | 14 |
| 7 | Geometrical characteristics | 14 |
| 7.1 | General..... | 14 |
| 7.2 | Measurement of dimensions..... | 14 |
| 7.3 | Dimensions of spigot ends for valves..... | 14 |
| 7.4 | Dimensions of valves with electrofusion sockets..... | 14 |
| 7.5 | Dimensions of the operating device..... | 14 |
| 8 | Mechanical characteristics of assembled valves and regional requirements | 15 |
| 8.1 | General..... | 15 |
| 8.2 | Conditioning..... | 15 |
| 8.3 | Requirements..... | 15 |
| 8.3.1 | Generals..... | 15 |
| 8.3.2 | Air flow rate..... | 20 |
| 8.4 | Regional requirement..... | 20 |

| | | |
|-----------|--|-----------|
| 9 | Physical characteristics | 21 |
| | 9.1 Conditioning | 21 |
| | 9.2 Requirement | 21 |
| 10 | Performance requirements | 21 |
| 11 | Technical File | 21 |
| 12 | Marking | 22 |
| | 12.1 General | 22 |
| | 12.2 Minimum required marking of valves | 22 |
| | 12.3 Additional marking | 23 |
| 13 | Delivery Conditions | 23 |
| | Annex A (normative) Determination of the leaktightness of seat(s) and packing | 24 |
| | Annex B (normative) Test method for leaktightness and ease of operation after tensile loading | 26 |
| | Bibliography | 28 |