

# ISO 871:2022-02 (E)

## Plastics - Determination of ignition temperature using a hot-air furnace

---

<b>Contents</b>		<b>Page</b>
Foreword		iv
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions</b>	<b>1</b>
<b>4</b>	<b>Principle</b>	<b>2</b>
<b>5</b>	<b>Apparatus</b>	<b>2</b>
5.1	Option 1 — Setchkin furnace	2
5.2	Option 2 – ISO 1182 refractory tube furnace	4
<b>6</b>	<b>Location of thermocouples</b>	<b>9</b>
<b>7</b>	<b>Test specimens</b>	<b>9</b>
<b>8</b>	<b>Procedure</b>	<b>10</b>
8.1	Flash-ignition temperature (FIT)	10
8.2	Spontaneous-ignition temperature (SIT)	11
<b>9</b>	<b>Precision</b>	<b>12</b>
<b>10</b>	<b>Test report</b>	<b>12</b>
<b>Annex A</b> (informative)	<b>Results obtained by interlaboratory trials using Option 1 (Setchkin furnace)</b>	<b>13</b>
<b>Annex B</b> (informative)	<b>Typical designs of test apparatus</b>	<b>15</b>
<b>Bibliography</b>		<b>17</b>