

# ISO 4437-4:2022-11 (E)

## Plastics piping systems for the supply of gaseous fuels - Polyethylene (PE) - Part 4: Valves

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>3.1</b>	<b>General .....</b>	<b>2</b>
<b>3.2</b>	<b>Terms relating to design .....</b>	<b>3</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>3</b>
<b>5</b>	<b>Material .....</b>	<b>3</b>
<b>5.1</b>	<b>Material for polyethylene parts .....</b>	<b>3</b>
<b>5.2</b>	<b>Material for non-polyethylene parts .....</b>	<b>4</b>
<b>5.2.1</b>	<b>General .....</b>	<b>4</b>
<b>5.2.2</b>	<b>Metal parts .....</b>	<b>4</b>
<b>5.2.3</b>	<b>Sealing materials .....</b>	<b>4</b>
<b>5.2.4</b>	<b>Greases and lubricants .....</b>	<b>4</b>
<b>5.2.5</b>	<b>Assembly .....</b>	<b>4</b>
<b>6</b>	<b>General characteristics .....</b>	<b>5</b>
<b>6.1</b>	<b>Appearance of the valve .....</b>	<b>5</b>
<b>6.2</b>	<b>Colour .....</b>	<b>5</b>
<b>6.3</b>	<b>Design .....</b>	<b>5</b>
<b>6.3.1</b>	<b>General .....</b>	<b>5</b>
<b>6.3.2</b>	<b>Valve body .....</b>	<b>5</b>
<b>6.3.3</b>	<b>Valve ends .....</b>	<b>5</b>
<b>6.3.4</b>	<b>Operating device .....</b>	<b>5</b>
<b>6.3.5</b>	<b>Seals .....</b>	<b>5</b>
<b>7</b>	<b>Geometrical characteristics .....</b>	<b>5</b>
<b>7.1</b>	<b>General .....</b>	<b>5</b>
<b>7.2</b>	<b>Measurement of dimensions .....</b>	<b>6</b>
<b>7.3</b>	<b>Dimensions of spigot ends for valves .....</b>	<b>6</b>
<b>7.4</b>	<b>Dimensions of valves with electrofusion sockets .....</b>	<b>6</b>
<b>7.5</b>	<b>Dimensions of the operating device .....</b>	<b>6</b>
<b>8</b>	<b>Mechanical characteristics of assembled valves .....</b>	<b>6</b>
<b>8.1</b>	<b>General .....</b>	<b>6</b>
<b>8.2</b>	<b>Requirements .....</b>	<b>6</b>
<b>8.2.1</b>	<b>General .....</b>	<b>6</b>
<b>8.2.2</b>	<b>Air flow rate .....</b>	<b>13</b>
<b>9</b>	<b>Physical characteristics .....</b>	<b>13</b>
<b>9.1</b>	<b>Conditioning .....</b>	<b>13</b>
<b>9.2</b>	<b>Requirements .....</b>	<b>14</b>
<b>10</b>	<b>Performance requirements .....</b>	<b>14</b>

<b>11</b>	<b>Technicalfile .....</b>	<b>14</b>
<b>12</b>	<b>Marking .....</b>	<b>15</b>
<b>12.1</b>	<b>General .....</b>	<b>15</b>
<b>12.2</b>	<b>Minimum required marking .....</b>	<b>15</b>
<b>12.3</b>	<b>Additional marking .....</b>	<b>16</b>
<b>13</b>	<b>Delivery conditions .....</b>	<b>16</b>
	<b>Annex A (normative) Determination of the leaktightness of seat(s) and packing .....</b>	<b>17</b>
	<b>Annex B (normative) Test method for leaktightness and ease of operation after tensile loading .....</b>	<b>19</b>
	<b>Bibliography .....</b>	<b>21</b>