

ISO 22183:2023-05 (E)

Plastics - Validation of force-time curves obtained from high-speed tensile tests

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 4 |
| 5 | Measurement of the natural oscillation spectrum of the grip and force transducer configuration | 5 |
| 5.1 | Measurement of natural oscillation frequencies | 5 |
| 5.1.1 | Set-up of the high-speed tensile equipment | 5 |
| 5.1.2 | Set-up of the striker | 5 |
| 5.1.3 | Measurement procedure | 5 |
| 5.2 | Determination of the natural oscillation spectrum | 6 |
| 6 | Validation | 7 |
| 6.1 | Minimum event time | 7 |
| 6.2 | Maximum allowed intensity | 8 |
| 7 | Test report | 9 |
| Annex A (informative) Configuration of the high-speed testing machine | | 11 |
| Annex B (informative) Example for the measurement of natural oscillation frequencies | | 15 |
| Annex C (informative) Influence of a set position on the natural oscillation spectrum | | 18 |
| Annex D (informative) Relation between the nominal test speed and the nominal strain | | 21 |
| Bibliography | | 23 |