

# ISO 8513:2023-07 (E)

## Plastics piping systems - Glass-reinforced thermosetting plastics (GRP) pipes - Test methods for the determination of the initial longitudinal tensile strength

---

| <b>Contents</b>       |  | <b>Page</b> |
|-----------------------|--|-------------|
| Foreword .....        |  | iv          |
| 1                     | Scope .....  | 1           |
| 2                     | Normative references .....   | 1           |
| 3                     | Terms and definitions .....  | 1           |
| 4                     | Principle .....  | 2           |
| 5                     | Apparatus .....  | 3           |
| 5.1                   | Tensile-testing machine .....  | 3           |
| 5.2                   | Grips .....  | 3           |
| 5.3                   | Dimension measurement devices .....  | 4           |
| 6                     | Test pieces .....  | 4           |
| 6.1                   | General .....  | 4           |
| 6.2                   | Strip test piece (method A) .....  | 4           |
| 6.2.1                 | Shape .....  | 4           |
| 6.2.2                 | Dimensions .....   | 4           |
| 6.2.3                 | Use of built-up ends .....   | 6           |
| 6.3                   | Pipe section test pieces (method B) .....  | 6           |
| 6.4                   | Number of test pieces .....  | 6           |
| 7                     | Conditioning .....   | 7           |
| 8                     | Test temperature .....   | 7           |
| 9                     | Procedure (methods A and B) .....  | 7           |
| 10                    | Calculation .....  | 7           |
| 10.1                  | For strip test pieces (method A) .....   | 7           |
| 10.2                  | For pipe test pieces (method B) .....  | 8           |
| 11                    | Test report .....  | 8           |
| Annex A (informative) | Determination of longitudinal properties for helically filament-wound thin wall pipe ..... | 10          |
| Bibliography .....    |  | 12          |