

ISO 16486-6:2023-10 (E)

Plastics piping systems for the supply of gaseous fuels - Unplasticized polyamide (PA-U) piping systems with fusion jointing and mechanical jointing - Part 6: Code of practice for design, handling and installation

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviated terms	2
	3.1 Terms and definitions	2
	3.2 Symbols and abbreviated terms	3
4	Design	4
	4.1 General and regional requirements	4
	4.1.1 General	4
	4.1.2 Regional requirements	4
	4.2 Materials, components and jointing equipment	5
	4.3 Maximum operating pressure	5
	4.3.1 General	5
	4.3.2 Maximum operation pressure based on long-term hydrostatic strength	5
	4.3.3 Maximum operation pressure based on rapid crack propagation	5
	4.4 Assembly techniques	6
	4.5 Squeeze-off properties	6
5	Construction	7
	5.1 Competence	7
	5.2 Storage, handling and transport	7
	5.2.1 General	7
	5.2.2 Storage	7
	5.2.3 Handling	8
	5.2.4 Transport	9
	5.3 Jointing	9
	5.4 Laying	9
	5.4.1 General	9
	5.4.2 Trench	10
	5.4.3 Drag forces	10
	5.4.4 Valves	11
	5.4.5 Connection to existing systems	11
	5.4.6 Backfilling	11
	5.4.7 Non-conventional installation	12
	5.5 Pressure testing and commissioning	12
6	Quality control	12
	6.1 General	12
	6.2 Inspection prior to laying	12
	6.3 Inspection during laying	13
	6.3.1 Laying	13
	6.3.2 Joint integrity	13
	Annex A (normative) Butt fusion jointing procedure	20
	Annex B (normative) Electrofusion jointing	25
	Annex C (normative) Mechanical jointing	31
	Annex D (informative) Squeeze-off and re-rounding	32

Annex E (normative) Derating coefficients for various operating temperatures35
Annex F (informative) Regional requirements for CEN member countries36
**Annex G (informative) Additional information for demonstrating the fitness of PA-U piping
systems for non-conventional installation techniques37**
Bibliography.....39